Approved For Release 2005/11/17 : CIA-RDP02T06408R000400010026-8

Top Secret



Imagery Analysis Report

Naro Fominsk Probable ABM Phased Array Radar Complex

25X1

Declass Review by NIMA/DOD


25X1

Top Secret

25X1

DDI/IAR 81007

DATE Sep 1967
COPY 45



COP			COPY NO.	PUB. DATE		LOCATION			MASTE	ER	DATE RECEIVED	LOCA	TION		
				ON DATE(S)				STOC			MINIMUM 1	MAXI	MUM	1	
CUT COP		0	DATE 7/7/4	CUT TO COPIES	1	DATE		COPI	ES DE	STROY	ED				
CUT COP			DATE	CUT TO COPIES		DATE									
CUT			DATE	MASTER		DATE									
	DATE				NUME	BER OF C	OPIES		DATE		NUMBER OF		R OF C	PIES	
MO.	DAY	YR.	RECEIVED OR	ISSUED	REC'	D ISS'D	BAL	MO.	DAY	YR.	RECEIVED OR ISSUED		REC D	Iss'p	BAL
rs '	19	68	Dist. Unit #2	. 7	1		1	<u> </u>							
10	3	68	NPIC #4	7		/	0								
		,													
								<u> </u>							
					-										
				<u> </u>											
								<u> </u>	 						
		ļ				-									
									ļ						
- 2 = 1								ļ							
25)	1											·			
717	LE N	PIC	IAR8	1007	S ^d pt	t. 196'	7		CLAS	ss.	LOCATION	25	109		 25X1
					-				<u>"</u>				-		

Approved For Release 2005/11/17: CIA-RDP02T06408R000400010026-8

MASTER

STOCK

DATE RECEIVED

MINIMUM

LOCATION

MAXIMUM

COPY NO.

PUB. DATE

DISPOSITION DATE(S)

LOCATION

RECORD COPY

			DISPOSIT	ION DATE(S)				STOC			MINIMUM	1	MAXIMUM	5	
UT OP I	-	0	DATE 10-73	CUT TO COPIES		DATE				STROYE	D				_
UT OP I			DATE	CUT TO COPIES		DATE									
UT OP I			DATE	MASTER		DATE									
D	ATE		RECEIVED OR	ACCUED	NUM	BER OF C	OPIES		DATE		DECE 145	D OR ISSUED	NUMBE	R OF C	PIES
<u>. </u>	DAY	YR.	RECEIVED OR	ISSUED	REC.	D ISS D	BAL	MO.	DAY	YR.	RECEIVE	D OK ISSUED	REC D	ISS'D	BAL
ιd	12	67	Dist. Unit	#39-43	5		5								
2	5	67	NPIC 3	9-43		5	0								
				•				į							
			<u> </u>												
1								†							
+								<u> </u>			· · · · · · · · · · · · · · · · · · ·				
1								-							
\dashv	\neg							-							
\dashv							·								
\downarrow								<u> </u>							
\dashv					<u> </u>			<u> </u>							
<u>5</u>															
1 TL	εN	PIC						SEC.	CLAS	s.	LOCATION				
				Ş	Sent	t. 196	57	r	's/		7	347	70		25)
	1 L			•		/ n	,		٠ _						20,

25X1	

TOP	SECRET	

September 125 X 1

Approved For Release 2005/11/17: CIA-RDP02T06408R000400010026-8

NARO FOMINSK PROBABLE ABM PHASED ARRAY RADAR COMPLEX

MARCH 1965 TO JUNE 1967

SUMMARY

The northwest-facing antennas at the Moscow Doghouse Radar Complex are probably externally complete, some five years since initial construction was identified, and about three years since the start of actual face construction. This degree of completion is seen at both the probable receiver and transmitter sites (Operations Areas A and B). The readiness of these antennas for initial operation will now depend on the amount of internal construction, equipment installation, and checkout remaining to be done.

The southeast-facing antennas at Operations Areas A and B are not yet complete. Their construction is approximately one year less advanced than that of the northwest-facing antennas.

The antenna faces of Doghouse A were found to be constructed in separate layers, installed over a heavy steel truss framework. The basic composition of the face consists of a vertical arrangement of adjacent, rod-like elements, over which is installed a thicker layer composed of diagonally-set, ten-foot square blocks.

An azimuth sector scan of about 60 degrees is indicated for the northwest-facing probable transmitter antenna, rather than the 90 to 100 degrees previously assumed. The 60-degree sector is suggested by tree removal in a fan-shaped pattern in front of the antenna, extending outward at 30 degrees to either side of boresight

No similar clearing activity has yet occurred in front of the southeast-facing antenna, probably because of its less advanced construction status.

The only visible source of external electric power for the Doghouse is supplied to the operations areas through a buried 6-to 10-kv line from the associated power substation. However, a 110-kv powerline passes nearby and possibly constitutes an additional source of power.

Construction at the associated complex support facilities is also nearing completion. Of specific significance are 17 large multi-story apartment buildings which constitute the permanent housing at the Doghouse complex. These buildings could accommodate at lenst 4,500 personnel, compared to accommodations for approximately 1,800 personnel at both Wishelevka (Angarsk) and Sary Shagan Site 13 Anti-Satellite/Space Tracking Radar Complexes.

25X1

25X1

DEY:	1	
25X	ı	
		l
		l

---25×1

CONTENTS

<u>Page</u>		
Summary		Page
Introduction	Figure 2. Narc Fominsk Doghouse Radar Complex and Related Facilities	4
Operations Area A	Figure 3. Relative Size Comparison Between Doghouse Radar A	
Doghouse Radar A	and Other Large Structures	5
Structural Analysis	Figure 4. Doghouse Operations Area A,	25X1
Construction Chronology	Figure 5. Unrectified Flan Drawing with Dimensions of Operations Area A	7
Construction Materials	Figure 6. Profile Dimensions of Doghouse Radars A and B	8
Related Facilities	Figure 7. Concept For Installation of Facing Material, Doghouse	
Operations Area B	Radar A	9
Doghouse Radar B	Figure 8. Doghouse Radar A.	¹25X1
Structural Analysis	Figure 9. Doghouse Radar A,	10
Construction Chronology	Figure 10. Doghouse Radar A,	10
Construction Materials	Figure 11. Doghouse Radar A,	11
	Figure 12. Doghouse Radar A.	11
Related Facilities	Figure 13. Doghouse Radar A.	11
Complex Support Areas	Figure 14. Major Types of Construction Materials Observed at	
Main Support Area	Doghouse Radar A	12
Construction Support Area	Figure 15. Doghouse Operations Area B,	¹25X1
Railroad Classification Yard	Figure 16. Unrectified Plan Drawing with Dimensions of Operations	
Power Substation	Area B	
Probable Water Treatment Facility	Figure 17. Doghouse Radar B,	¹25X1
References	Figure 18. Artist Concept of Doghouse Radar B Construction	
	Figure 19. Doghouse Radar B,	¹95¥1
<u>Tables</u>	Figure 20. Unrectified Line Drawing of Main Support Area and Railroad	25/(1
Table I. Structures in the Main Support Area and Railroad Classification	Classification Yard	17
Yard (keyed to Figure 20)	Figure 21. Main Support Area and Railroad Classification Yard,	19
Table II. Structures in the Construction Support Area (keyed to Figure 23)	Figure 22. Construction Support Area,	25X1
	Figure 23. Unrectified Line Drawing of Construction Support Area	25X1
Illustrations		
Figure 1. Location of Naro Fominsk Doghouse Radar Complex,	Figure 24. Unrectified Line Drawing of Power Substation	22
USSR	Figure 25. Power Substation,	°25 X 1

TOP SECRET

25X1

25×1

25X1

25X1

TOP SECRET Approved For Release 2005/11/17: CIA-RDP02T06408R000400010026-8

2\$X1

INTRODUCTION

This study presents a photographic analysis of the This study presents a protographic analysis of the Naro Fominsk Probable ABM Phased Array Radar (Doghouse) Complex, with emphasis on mensural and structural analysis of the radar antennas. It also constitutes an update of the associated facilities, showing their chronological development since

The haro Fominsk Probable ABM Phased Array Radar (Doghouse) Complex is located about 35 mautical miles (nm) southwest of Moscow and consists of two separate operations areas and associated support facilities (Figures 1 and 2). The larger of the two operations areas (Operations Area A) contains the large A-frame antenna structure, Doghouse A; the smaller area (Operations Area B) is located approximately 8,000 feet west-southwest of Area A, and contains two smaller linear antennas, Doghouse B. antennas, Doghouse B.


All mensuration in this report has been performed by the MTC Technical Intelligence Division, unless otherwise indicated, and is considered accurate within the stated limits. Since some mensuration in this report differs from previously published measurements, the basis for the refinements and the present degree of confidence is as follows: the small refinements in antenna hornstand all and elevation angle degrees) were felt to be justified, since previous figures foll in the outer parameters of the narrow range of latest results to be computed from numerous large and missions.

Correlation between antenna measurements computed from four separate large-scale missions resulted in a greater degree of confidence than previously obtained. Advances in computer systems and methods, plus a close coordination between the imagery analyst and the photogrammetrist to derive the most accurate results, also increases this confidence.

For the purposes of this report, the facilities previously termed Support Area A and Support Area B have been redesignated Construction Support Area and Main Support Area, respectively, to better identify their functions.

OPERATIONS AREA A

Operations Area A is located in the southeast corner of the complex (Figure 2). The major structure in the area is a large A-frame antenna structure (loghouse A), which has been under construction for over three years. Other permanent facilities include a control building, a T-shaped earth-mounded structure, and a steam plant. A photograph and drawings with detailed mensuration of the structures in Operations Area A are shown in Figures 4, 5, and 6.



Approved For Release 2005/11/17: CIAºRDP02T06408R000400010026-8


TOP SECRET

25X[

TOP SECRET

25×1

Approved For Release 2005/11/17 : CIA-RDP02T06408R000400010026-8



25X1

Approved For Release 2005/11/17₄; CIA-RDP02T06408R000400010026-8
TOP SECRET

Figure

25X1

25X1

25X1

TOP SECRET

25×2

Approved For Release 2005/11/17: CIA-RDP02T06408R000400010026-8

Doghouse Radar A

This is a large A-frame antenna structure, 400 feet square at the base and 360 feet high [Figures 5 and 6). It supports two 345 by 365-foot probable receiver antennas, one facing north-northwest and the other south-southeast. Both have boresight elevation angles of 25 degrees. A comparative graphic, showing the size of Doghouse A relative to other large, more familiar structures, i shown in Figure 3.

of Degiouse A relative to other large, more familiar structures, is shown in Figure 3.

Structural Analysis. The basic skeleton of the Deghouse A radar is formed by the use of heavy steel truss members. These members are emplaced in two opposing rows to create the load-bearing frame or surface plane of each face on the A-frame structure (Figures 4 and 8). Each of the surface planes is vertically subdivided by 19 truss members, spaced at 20-foot intervals. These divide the face opening into 20 vertical openings or "slots," each with a width of 20 feet. The 19 truss members within each face plane converge inward toward an apex at angles of 25 degrees. At the top, thoy are attached to a flat, probably solid roof, and 400 feet long (Figures 5 and 6). Joined to the load-bearing truss members within each face opening are allowed to the load-bearing truss members within each face opening are 18 horizontal braces or purlins, vertically spaced at 20-foot intervals. There is indication on several ground photographs that these horizontal braces possibly alternate in thickness, mine thick and nine thin. The resulting broadside configuration is that of a steel grid, 400 feet wide and 360 feet high, composed of 380 twenty-foot squares. The thickness or depth of the face frame is approximately ton feet. Diagonal steel members and further structural support to the main trusswork on the face of the antenna. These are most prominently noted across the open border between the top of the antenna face and the roof of the structure. The diagonal members are installed at one per each 20-foot division at alternating 45-degree angles. Although no other diagonal bracing can be as clearly identified as that above the face, there are indications from ground photography of additional diagonal bracing within the overall face. It is assumed, therefore, that such members are probably present throughout the face structure.

The southeastern face was observed on and and it was noted through shadow analysis that sunlight did not pass through the yet-uncovered framework fin the lower half of the face. A comparison with earlier photography, where sunlight did pass completely through the structures, suggests that a closely spaced arrangement of braces is installed within the tenfoot depth of the main trusswork during preliminary construction. This additional bracing would probably serve for mounting electronic components and/or facing material and might provide additional structural support.


Also evident prior to the installation of facing material, is one probably thickly Intticed 20-foot-wide column or shart in each side of the open face, approximately 40 feet in from the end walls. Each of these columns appears to be constructed between a pair of main vertical truss members. It is possible that these columns could be either open elevator shafts providing interior access to the antenna screen, lift mechanism housings for interior scaffolding, or functional parts of each antenna face.

The end walls of the A-frame are constructed of a solid material of undetermined thickness and are probably supported by a superstructure which is more massive than the inclined truss members within the face opening. The outer edges of the end walls on both sides of the A-frame extend approximately nine feet past the surface plane created by the inclined trusses (Figure 6). This would allow a maximum usable depth of for application of face layers, assuming the final layor to be on an inclined plane coincident to the outer edges of the end walls. A wedge-shaped section appears to have been purposely emitted from the outer edge of the base along both sides for the full length of the structure (Figures 5 and 6). This omission may be a temporary feature for construction access, or a part of the original design. No accurate measuration is currently available for this section; however, based upon existing measurements and photo analysis, it appears that the bare of the outer edge is approximately 30 feet above ground level. The result is a vertical wall 30 feet high which has been observed under construction and appears to meet the outer edge of the base of the end wall. This feature is illustrated in Figure 6.

Photography of permittee identification of a rew of V-shaped probable counterbraces within the A-frame structure (Figures 7 and 9). The foundations for these counter-braces are set at 20-foot intervals, parallel to the base of the main truss

members, and probably extend the full length of the antenna on both sides. The V-bracea extend 60 to 70 feet back from the main truss wember foundations in the scatheastern face opening. The tops of the "V" span a 20-foot width, equal to the width of the main vertical divisions in the antenna face. Lack of accurate mensuration precluded a determination of where or how the V-bracea are attached to the inner face frame. It appears, however, that they are intended to counter the 25X1 25-dagree slope of the main truss members in the face. The inside of the northwestern face has never been photographed from an angle which would allow identification of similar counter-bracing there; however, it is presumed that construction of both faces is identical.

On numerous ground photographs, indications of major diagonal members have been observed within the A-frame structure prior to installation of facing materials. This also suggests that within the interior of the Dojhouse radar, a complex arrangement of bracing and counter-bracing may be present, stabilizing the structure as a whole.



RELATIVE SIZE COMPARISON BETWEEN DOGHOUSE RADAR A AND OTHER LARGE STRUCTURES.

Approved For Release 2005/11/17 : CIA-RDP02T06408R000400010026-8

25X1


Figure 3

25X1_____

TOP SECRET

___25X1


Approved For Release 2005/11/17 : CTA-RDP02T06408R000400010026-8




Approved For Release 2005/19/17 Post CFA RDP02T 06408R000400010026-8

TOP SECRET

Figure 425X1






25X1-----

TOP SECRET

25×1

Approved For Release 2005/11/17 : CIA-RDP02T06408R000400010026-8



Approved For Release 2005/11/17: CIA-RDP02T06408R000400010026-8

Figure 7

25X⁻

25X1

25X1

25×1

25X1

25X1

25X1

25X1

Approved For Release 2005/11/17: CIA-RDP02T06408R000400010026-8

TOP SECRET

(or diameter), begins at the top of the antenns face (approximately 20 feet below the roof level) and progresses downward toward the base in even strips across the antenna face. Once completely installed, the elements extend vertically from the top of the base of the [Sant height) antenna face; however, these rod-like elements may not extend completely to the edge of the completed screen.

edge of the completen screen.

b. Layer 2 (Possible), Facing Materials. This layer appears light toned on photography and is probably of a smooth texture. The appearance of this layer consistently occurs some distance below or in advance of the descending construction progress of the elements in Layer 1 (Figure 7). However, since this light-toned material disappears when the rod-like members become visible in the same location, it is believed that this possible second layer could actually be a series of individual "package" units. Each unit could contain segments of the rod-like elements which form Layer 1. Assuming this to be the case, the light-toned package units containing these elements would actually be the first material to be attached to the face, the package or covering then being systematically removed from each unit, exposing the vertically-striated signature of the rod-like elements. This light-toned layer, however, cannot be discounted as a separate functional layer.

A departure from this construction tachnique was observed on the northwestern face on local strip of probable light-toned package units (Layer 2) was in place across the base of the A-frame superstructure for a horizontal distance of 345 feet. Yet to be installed was one 20-foot wide segment on the northern end. By additional face layers were installed across the total width of the antenna face (365 feet), from the top down to a point approximately 20 feet above the previously observed 45-foot strip at the base. The result was an approximately 20-foot high lateral gap across the face. This opening remained for about a year until large-scale photography of revealed that the gap had been filled.

c. Layer 3, Facing Materials. Layer 3 (Figure 7) appears to consist of a series of sections probably ten-feet square and installed over the vertical rod-like elements (Layer 1), and is probably the thickest of the four layers. The probable square sections are light toned and are installed, commencing at the top, in lateral rows across the antenna face. Each square section is set at 45-degree angle from the horizontal. The resulting configuration, during construction, is a saw-tooth pattern formed along the horizontal row being installed, as shown in Figures 7 and 10. A ten-foot wide column is constructed along the vertical borders of the face. It is apparently made of the same type material as the ten-foot squares, but with no evidence of a diagonal or saw-tooth pattern. or saw-tooth pattern.

To completely cover the near-square (fee antenna face with these diagonally set blocks, the squar sections should be supplemented, possibly by similar type triangular sections which would allow a smooth and even border around the face. This leads to the assumption that roughly 1,200 of the ten-foot square sections, plus possible triangular sections, would be needed to completely cover the 124,630-square-foot sur-

face of each antenna face. Though it appears that the ten-foot square sections are the most likely basic element for Layer 3, it is possible that triangular or other quadragular-shaped sections could also fit within the construction format being followed in this layer.

d. Layer 4, Facing Material. Layer 4 (Figure consists of a smooth light toned material forming a 20-foot-wide border along the top and both sides of the antenna structure. Although this border appears to overlap the antenna face by several foot, it does not seem to relate to the operation of the radar itself. Layer 4 (Figure 7)

Construction Chronology. A complete and comprehensive chronology of the construction of individual face layers is precluded since only missions provide clear large-scale coverage of Dognouse A prior to However, information obtained from this photography is However, information obtained from the provided in the following chronology.




Figure DOGHOUSE RADAR A

a. Northwest Face. The first firm evidence of face layer installation on either of the two antenna faces was seen on time, a 345-foot strip of material, approximately 45 feet high, was observed across the lower edge of the northwestern face. The strip possibly consisted of the rod-like elements (layer 1) encased within a smooth-textured material (layer 2). From the possible arrangement of layers I and 2 had been installed from the top of the antenna face down to a point approximately 20 feet above the existing strip at the base, leaving a 20-foot gap across the lower portion of the face. At the same time, it was noted that the light-toned material (Layer 2) had probably been removed from a portion of the top of the antenna face and elements of Layer 3 were being installed on top of the exposed rod-like elements. One row of the probable ten-foot square sections (or perhaps triangular half sections) had been installed across the top of the face to within 40 to 50 feet of the left edge. At that point, installation of a second row had progressed back to about the center of the antenna face.

A vertical border, probably of Layer 3 material, had been constructed along the left and right edges of the face with a break at the lateral gap near the lower edge.

Layer 2 had been removed from the top of the antenna face downward for more than half of the height of the face, leaving the rod-like signature of Layer 1. No progress had been made on Layer 3 across the top since liowever, several probable solid gray sections, possibly Layer 4, were present above the face 25X1 opening, to the left of center.



DOGHOUSE RADAR A Figure25X1

25X1 AME STATEMENT 25X1 DOGHOUSE RADAR A,

Approved For Release 2005/11/17: CIA-RDP02T06408R000400010026-8

TOP SECRET

TOP SECRET

IMAGERY ANALYSIS SERVICE Approved For Release 2005/11/17: CIA-RDP02T06408R000400010026-8

25X1

Between no conclusive interpretation of the northwestern antenna face could be performed due to unfavorable camera angles and poorquality, cloud-covered photography. During this period, however, the lateral gap in the lower portion of the face was filled.

25X1

The clearest large-scale photography of the Doghouse radar to date, was on several passes from Unfortunately, on the clear passes the northwestern face was in dark shadow (Figure 11). Fwident, however, was the installation of the antenna border (Layer 4) across the base and halfway up the right side of the face opening. Although the antenna face was in shadow, this photography also revealed a large section in the lower right corner of the face to be of a somewhat darker tone than the remainder.



DOGHOUSE RADAR A,

25X1

25X1 25X1

On a series of ground photographs taken in vertical borders were observed extending to the top of the face, but not all the way to the roof.

Several possible border sections previously seen above the face were not noted on this photography. The vertical borders appeared slightly lighter in tone than the actual face, possibly indicative of some degree of translucence.

Figure 11

Good-quality but small-scale photography during the summer and fall of 1966 did not permit antenna layer details to be seen.


25X1

The facility was next observed on large-scale photography on _____ Though the camera angle and weather conditions were unfavorable for obtaining additional detail in face construction, all previous interpretations were confirmed.

Succeeding small-scale missions were also of insufficient scale and resolution for further detailed 25X1 interpretation.


25X1

provided the most recent large-scale photography of the facility. Three passes pro-vided interpretable photography, though all were nonstereo.



DOGHOUSE RADAR A.

Photography of the quality. The other two passes were identical to the quality. The other two passes were identical to the photography in both camera angle and time of day. The northwestern face was in shadow on all three passes, and no significant developments were visible. Only scattered remnants of the previously observed construction material remained in the cleared area in front of the morthwestern face.



DOGHOUSE RADAR A,

Figure 13

It is likely that the northwestern face is nearing completion and that little more construction detail will be observed from photography. Initial operation of the northwestern face can probably no longer be gauged by external construction progress. The complexity of interior construction has now become the principal factor governing this consideration. It should be noted, however, that similar large Soviet radars have become active, though not necessarily operational, before

external face panel installation or modifications had been made (i.e. Hen House).

b. Southeast Pace. The first evidence of face material installation over the southeastern face opening was observed on the alight-toned material was present across the upper part of the face. Due to the small seed of the photography, however, the extent or type of covering could not be determined.

By state and this material probably extended over the greater portion of the top 25X1 of the face.

scale photography of the southeastern face (Figure 4). 25X1
From this photography, the installation of rod-like
elements in Layer I was clearly evident over approximately half of the face area. A light-toned, vertical
20-foot-wide border (probably Layer 2) was present on
each side of the antenna face. In addition, probable
Layer 2 material was also present below the visible rodlike elements, in a 30-foot-wide strip which extended
completely across the face. A wide scaffold, at least
36 feet long, was suspended from the roof to about the
point where construction had progressed. A smaller
probable scaffold was visible against the background
of the elements in Layer 1. Construction progress during
the five-day period between the two passes on Mission
was as follows. On the light-toned border
of Layer 2 material below the elements of Layer 1 was
not yet complete, and several light-toned sections were
present on the ground in front of the antenna. By
however, the border had been completed, and the
sections lying on the ground had disappeared. A 40-foot
section of border or framing material (Layer 4) was
also observed in place on the upper left corner of the
face opening.

by antenna con-struction had progressed slightly, and the extent of the 25X1 border above the face had been increased to more than half the distance across the face opening.

On a face construction had advanced to within 150 feet of the base. The border above the face appeared complete, although the center portion was noticeably darker in tone than the

First evidence of the installation of Layer 3 material on the southeastern face was observed on with approximately 50 to 75 feet of the thick, light-toned layer present 25X1 across the top of the face. However, no vertical border of Layer 3 material, such as seen during similar construction on the northwestern face, was present. Construction of the Layer 1 elements had progressed to within 100 feet of the base.

confirmed the activity previously observed. The only progress seen at this time was the installation of Leyer 1 elements to within about 20 feet of the base. It was also noted that the previously completed border section above the face had assumed an interrupted pattern, as if portions had been removed.

feet of the base.

Approved For Release 2005/11/17 :: CIA-RDP02T06408R000400010026-8 TOP SECRET



TOP SECRET

Approved For Release 2005/11/17: CIA-RDP02T06408R000400010026-8

25X1

No further progress on the face could be confirmed unit photography of revealed the upper half of the face to be covered by Layer 3. Also at this time, the elements of Layer 1 had probably been completed to the base limits of the face. A dark-gray covering was present in the border area between each edge of the face and end walls.

25X1 25X1

The advancing construction of Layer 3 toward the base of the southeastern antenna was observed most recently on Only the northwestern face of Doghouse A was observed on Mission (Figure 13).

It is believed that no more than a year should be required to advance the southeastern face to a state of external completion equal to the present status of the northwestern face.

25X1

Construction Materials. Since the amount of construction material in front of the north-western face of the Doghouse A radar has decreased steadily as construction on the antenna progressed. By the end of 1966, only scattered pieces of material remained in the area. A considerable amount of stacked construction material still remains in front of the southeastern face, although it too is disappearing as construction progresses.

While the types of construction materials vary, there appear to be four common sizes which have consistently been observed (Figure 14). The largest of the four (Figure 14a) is approximately rest and is possibly some type of packing crate or container. It usually appears light toned and is frequently seen with a diagonal section removed from one end. Of similar size, but probably a foot or so shorter, is a rectangular object (Figure 14b) of varying shades of gray. At least one of these objects was observed partially encased within the light-toned larger crate (Figure 14a) in front of the southeastern antenna face. This object could be, or contain, a group of smaller pieces of material, as suggested by frequently observed differences in height and by the presence of nearby light-toned material on the ground.

Another item (Figure 14c) is a object similar in appearance to a canvas-covered trailer. The object is susually dark in tone. The smallest of the four objects (Figure 14c) is an approximately square of material, most often seen during final stages of construction and appearing in stacks of various heights. In addition, numerous other pieces of unidentified construction material have appeared in the cleared

Related Facilities. The support elements in Operations Area A (Figure 4) consist of a large L-shaped control building, an earth-mounded T-shaped structure, and at least ten smaller structures of a miscellaneous or construction support category. Also present are a

steam plant, a pumphouse, three earth-mounded liquid storage tanks, a bank of two cooling towers, and several cranes. Mensuration for these elements is shown in 25X1

a. Control Building. This L-shaped structure is located 70 feet from the western 25X1 side of Doghouse A and appeared complete in [Figure 4]. The main part of the building is 560 feet long and 180 feet wide, with a 165 by 100-foot wing on one end. A main personnel entrance is present in the southwest end of the building, and at least three possible vehicle entrances are visible around the structure. Eight objects of various sizes are located on the roof, the most significant of which appears to be a possible 15-foot-diameter dome-like structure on the southwest corner. The remaining seven objects are probably related to internal building functions or activities.


Two ten-foot-wide possible elevated cableways extend from the northeast wall of the control building to an 25X1 undetermined point within the A-frame structure. These are 35 feet above the ground and are supported on lattice columns.

b. T-Shaped Earth-Mounded Structure. A
T-shaped, earth-mounded structure of unknown function
is located northwest of the control building (Figure 4).
This is one of four such structures identified in the
Moscow area. It was completed by _____ and remains 5X1
unchanged to date. The other three of the six deployed
ARM launch complexes (R-O5, E-24, and E-33). The
facility at the Name Fominsk Radar Complex consists of
three earth-mounded rectangular structures which extend
outward from a 25-foot-high central bay to form a Tshaped configuration. This structure, with a small
parking area near its entrance, is the first facility
encountered upon entering the main gate. The front
entrance into the unmounded central bay of the T-shaped
structure appears to handle considerably more traffic
than the larger opening in the "stem" or northermmost
end. The road to the rear entrance has remained unsurfaced though it is wider than the road to the front
entrance and appears to be able to handle large, heavy
vehicles.

The two mounded sections paralleling the site access road are probably the main functional components of the facility and are vented on the extreme ends. The shortest of the three sections appears to be a possible drive-in loading or receiving wing for the other two sections.

c. Utilities. All of the heating and water pumping facilities in the area were probably still under construction in not becoming completely operational until late 1966. The principal components 2.5 X 1 the facility include the steam plant, a pumphouse, two water cooling twers, three earth-mounded liquid storage tanks, and a probable storage/maintenance building. Mensuration and photographs of these structures are provided in Figures 4 and 5.

d. Construction Granes. Two large jib or portal-type cranes have been associated with the construction of the Doghouse (Figure 4). The cranes were $25X1\,$



MAJOR TYPES OF CONSTRUCTION MATERIALS OBSERVED AT DOGHOUSE RADAR A,


Figure 14 Approved For Release 2005/11/17: CIA-RDP02T06408R000400010026-8

TOP SECRET

TOP SECRET


<u>2</u>5×1

Approved For Release 2005/11/17 : CIA-RDP02T06408R000400010026-8



Approved For Release 2005/11/17₋₁₃CIA-RDP02T06408R000400010026-8
TOP SECRET

Figure 1525X1



2 5×1
a smooth is material in a ten- with a mna quently to pro- on the stern
structures is are as of upon the 25X1
ma 25X1
ne physical enna minal puse radar.
ers, other th end of tion con-
radar pro- thwestern north- externally around time, 25X1 ad had One ilel to the
antenna estern estern 25×1 ees were 25×1 western 25×1
e of sight noce, the Ly small 25 1 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1
ma, most on stetus. At the control of the control
ino can take

Approved For Release 2005/11/17 : CIA-RDP02T06408R000400010026-8

TOP SECRET

25X1

25X1

25X1

25X1 25X1

25X1

DOGHOUSE RADAR B Figure 19

appear to be variations of a basic rectangular component approximately which is either truncated or segmented into triangular units. The triangular segment or unit averages approximately feet.

Once installed on the antenna, the location of these sections is undetermined. The most probable location is on the face, as paneling material, since no other types of material are present to be used for such purposes. Also possible is their use as roof sections, although this seems less likely.




Since the antenna faces are not vertically segmented or panelled as are Hen House antenna faces, no antenna details can be observed once the face is covered.

Related Facilities. the supporting facilities within Operations Area B were probably still under construction. At that time, they included a control building, a steam plant, pumphouse, three mounded liquid storage tanks, a security building and several construction support buildings (Figures 15 and 16).

a. Control Building. Both of the antenna structures are joined to a central control building by a pair of clevated, 15-fort-wide possible cableways (Figure 18). The building is 65 feet long, 200 feet wide, and where the main entrance is located. It was externally complete in _______ The presence of docrways, or openings, was observed in _______ in the lower level of the southern wall for all but approximately 100 feet of the length of the building (Figures 15 and 18). A dark tone along the lower level of the building observed on the latest photographic coverage, indicates that this open area is probably still present in both sides of the control building facing the rear of the antenna structure. Two "niches" or inset areas are present in identical locations in the upper portions of both side walls.

Among six structures on the roof is a 15-foot-diameter dome or dome-like object similar to that seen upon the roof of the control building for the Doghouse A

An L-shaped structure, located at the south end of the control building midway between the two antenna



ARTIST CONCEPT OF DOGHOUSE RADAR B CONSTRUCTION.

Figure 18

structures, was first observed under construction in ______ The structure consists of one 75-foot wing plus an adjoining 115-foot wing which is oriented perpendicular to the antennas. Each wing is approximately 15 feet wide. In ______ a 15-foot-diameter tank, or circular pedestal, was observed to the corner of the wing closest to the control building (Figure 19). 25X1 25X1 b. Steam Plant and Other Structures. The permanent utility-type structures including the steam plant, pumphouse, and liquid storage tanks appeared complete and operational by A bank of three cooling towers constructed since also appeared complete and operational by 25X1 25X1 25X1 Four construction support buildings were present in the vicinity of the antenna structures (Figure 17) in three of these structures, which would have fallen within the fan-shaped cleared area 25X1 in front of the northwestern antenna, had been removed. 25X1 structure had been constructed southwest of the antennas. In the same period, a small possibly operations-related structure was also constructed between the steam plant 25X1

COMPLEX SUPPORT AREAS

The complex support areas consist of a large main support and housing area, a construction support area, railroad classification yard, power substation, and a probable water treatment facility (Figure 2).

and the northwestern antenna structure.

Main Support Area

The Main Support Area (Figures 20, 21, and Table I), containing the housing, administrative/technical facilities, and two motor pools, is located about one mile north of Operations Area A along the main highway linking the towns of Naro Fominsk and Kubinka. In a total of eleven four-story apartments had either been completed or were still under construction in the area. By probably the last of 17 apartments were nearing completion, each of which could accommodate over 250 personnel (at 150 square feet per person). A large interconnected three-section structure (Figure 20, Item 15) has also been constructed west of the southernmost apartment building.

In the centrally located administration/technical area, four buildings (Figure 20, Items 27, 35, 37, and 50) have been added since All of these appeared externally complete by

A separate housing area containing probable wood frame dwellings of various sizes is located west of the rail line. The only significant change here since has been the removal of one of the larger dwellings, between

On approximately 100 miscellaneous vehicles were present within the two fenced motor pool areas. Five days later, no more than 20 vehicles remained.

TOP SECRET Approved For Release 2005/11/17: CIA-RDP02T06408R000400010026-8

25X1

25X1 25X1

25X1 25X1


25×1

25X1 25X1

TOP SECRET

25×1

Approved For Release 2005/11/17 : CIA-RDP02T06408R000400010026-8



UNRECTIFIED LINE DRAWING OF MAIN SUPPORT AREA AND RAILROAD CLASSIFICATION YARD.

Figure 20

X1

а	6	¥	1

TOP SECRET
Approved For Release 2005/11/17 - CIA-RDP02T06408R000400010026-

25X1

TABLE I

STRUCTURES IN MAIN SUPPORT AREA AND RAILROAD CLASSIFICATION YARD (Item numbers keyed to Figure 20)

Description Dimensions (Feet)* Dimensions (Fe						
Multi-Story Apartment Buildings				Item	Description	Dimensions (Feet)*
Multi-Story Apartsont Baildings	Item	Description	Dimensions (Feet)*			
2 Multi-Story Apartment Buildings Lo by 200		36-31-1 Ot 4	ho 2 000			
Multi-Story Apartson: Buildings						
Malti-Story Apartment Buildings b) by 260 50 biddentified 40 by 26						
Multi-Story Apartment Buildings b) by 260					Administration/Technical Support	
Multi-Story Agartment Buildings					Unidentified	45 by 50
Multi-Story Apartment Buildings					Unidentified	45 by 60
Multi-Story Apartment Buildings				52	Unidentified	40 by 85
Multi-Story Agartment Buildings 40 by 260						65 by 265
Mail:Story Apartment Buildings				54-63	Wooden Barracks	
Authorstory Apartment Buildings					Support	
Math-Borny Agartment Buildings				65	T-Shaped Messhall	
12				66	Storage	
Multi-story Apartment Buildings 40 by 260 66 Vehicle Storage 1Normal Linear Partment Buildings 40 by 260 69 Barracks 40 by 145				67	Storage	
Three-Section, Interconnected (a) is by 05 Three-Section, Interconnected (b) is by 120 The Structure (c) is by 120 The Structure (d) is by 120 The Structure (e) is by 120 The Structure (fine the Structure	13			68		
Three-Section, Interconnected (a) 15 by 05 70 Barracks 30 by 50	1.4			69	Barracks	40 by 145
Structure	15				Barracks	
Co		Structure	(b) 45 by 120			
10						
				73	Barracks	
Marter Standarde	17				Barracks	
19				75	Barracks	
Mail Story Apartment Building 40 by 260 76 Barracks 30 by 50				75	Barracks	
Construction Support Structure				76		
22						
23 Construction Support Structure Variable 79 Storage 25 by 30				78		
Construction Support Structure 25 by 50	23			79		
Construction Support Structure 20 by 100 81		Construction Support Structure		86		
Construction Support Structure		Construction Support Structure		81	Vehicle Storage/Maintenance	
27				82		
Two-Section, 1-Shaped Support Structure				83		
Possible Maintenance 75 by 145	28		60 by 115, 50 by 70	84	L-Shaped Sotrage	
Multi-Story Apartment Building 40 by 185 Railroad Classification Yard					•	
Multi-Story Apartment Building						
Multi-Story Apartment Building				Railr	oad Classification Yard	
(b) 35 by 100 (c) 35 by 100 (d) 36 Unidentified (e) 35 by 35 (d) 35 by 90, 50 by 185 (d) 35 by 90, 50 by 185 (e) 33 Administration (f) 45 by 100 (f) 46 by 100 (f) 47 by 100 (f) 48 by 100 (f) 49 by 100 (f) 40 by 100 (f) 41 by 100 (f) 42 by 100 (f) 43 by 100 (f) 45 by 100 (f) 46 by 66 (f) 47 by 100 (f) 48 by 100 (f) 49 by 100 (f) 40 by 100 (f) 40 by 100 (f) 41 by 100 (f) 42 by 100 (f) 43 by 100 (f) 44 by 100 (f) 45 by 100 (f) 46 by 100 (f) 47 by 100 (f) 48 by 100 (f) 49 by 100 (f) 49 by 100 (f) 40 by 100 (f) 41 by 100 (f) 42 by 100 (f) 43 by 100 (f) 44 by 100 (f) 45 by 100 (f) 46 by 100 (f) 47 by 100 (f) 48 by 100 (f) 49 by 100 (f) 40 by 10						
(c) 35 by 35 (d) 35 by 35 (d) 35 by 36 (d) 35 by 36 (d) 35 by 30, 50 by 185 (d) 34 U-Shaped Administration Building 75 by 169 (Overall) 90 Storage (d) by 170 (d) 170	32	Irregularly Shaped Structure	(a) 35 by 70		Possible Administration	45 by 100
(c) 35 by 35			(b) 35 by 100		Unidentified	20 by 60
Administration			(c) 35 by 35		Storage	
Administration 45 by 100 89 Storage 20 by 40			(d) 35 by 90, 50 by 185		Storage	
37 Administration/Technical 50 by 250 93 Storage 40 by 165 38 Administration/Technical 45 by 110 94 Unidentified 40 by 125 39 Administration/Technical 50 by 250 95 IShaped Support 50 by 90 Overall 40 Possible Athletics-Associated 65 by 65 96 Storage 40 by 170 41 Vehicle Maintenance 65 by 67 97 Storage 40 by 170 42 Storage 30 by 60 98 Storage 40 by 65 43 Equipment Storage 45 by 65 99 IShaped Storage 40 by 65 44 Steamplant 40 by 120 (Stack - 80) 100 Storage 20 by 65 Overall 45 Storage 46 by 65 99 IShaped Storage 20 by 65 Overall 46 Storage 47 by 120 (Stack - 80) 100 Storage 20 by 65 Overall 47 Storage 48 Storage 49 by 120 (Stack - 80) 100 Storage 20 by 65 Overall 48 Storage 49 by 120 (Stack - 80) 100 Storage 20 by 65 Overall 49 Storage 10 by 120 (Stack - 80) 100 Storage 20 by 65 Overall 40 Storage 20 by 65 Overall 41 Storage 20 by 65 Overall 42 Storage 30 by 65 Overall 43 Storage 30 by 65 Overall 44 Storage 30 by 65 Overall 45 Storage 30 by 65 Overall 45 Storage 30 by 65 Overall 46 Storage 30 by 65 Overall 47 Storage 30 by 65 Overall 48 Storage 30 by 65 Overall 49 Storage 30 by 65 Overall 40 Storage 30 by 65 Overall 40 Storage 30 by 65 Overall 40 Storage 30 by 65 Overall 41 Storage 30 by 65 Overall 42 Storage 30 by 65 Overall 41 Storage 30 by 65 Overall 42 Storage 30 by 65 Overall 43 Storage 30 by 65 Overall 44 Storage 30 by 65 Overall 45 Storage 30 by 65 Overall 45 Storage 30 by 65 Overall 45 Storage 30 by 65 Overall 46 Storage 30 by 65 Overall 47 Storage 30 by 65 Overall 48 Storage	33			89	Storage	
37 Administration/Technical 50 by 250 93 Storage 40 by 165 38 Administration/Technical 45 by 110 94 Unidentified 40 by 125 39 Administration/Technical 50 by 250 95 IShaped Support 50 by 90 Overall 40 Possible Athletics-Associated 65 by 65 96 Storage 40 by 170 41 Vehicle Maintenance 65 by 67 97 Storage 40 by 170 42 Storage 30 by 60 98 Storage 40 by 65 43 Equipment Storage 45 by 65 99 IShaped Storage 40 by 65 44 Steamplant 40 by 120 (Stack - 80) 100 Storage 20 by 65 Overall 45 Storage 46 by 65 99 IShaped Storage 20 by 65 Overall 46 Storage 47 by 120 (Stack - 80) 100 Storage 20 by 65 Overall 47 Storage 48 Storage 49 by 120 (Stack - 80) 100 Storage 20 by 65 Overall 48 Storage 49 by 120 (Stack - 80) 100 Storage 20 by 65 Overall 49 Storage 10 by 120 (Stack - 80) 100 Storage 20 by 65 Overall 40 Storage 20 by 65 Overall 41 Storage 20 by 65 Overall 42 Storage 30 by 65 Overall 43 Storage 30 by 65 Overall 44 Storage 30 by 65 Overall 45 Storage 30 by 65 Overall 45 Storage 30 by 65 Overall 46 Storage 30 by 65 Overall 47 Storage 30 by 65 Overall 48 Storage 30 by 65 Overall 49 Storage 30 by 65 Overall 40 Storage 30 by 65 Overall 40 Storage 30 by 65 Overall 40 Storage 30 by 65 Overall 41 Storage 30 by 65 Overall 42 Storage 30 by 65 Overall 41 Storage 30 by 65 Overall 42 Storage 30 by 65 Overall 43 Storage 30 by 65 Overall 44 Storage 30 by 65 Overall 45 Storage 30 by 65 Overall 45 Storage 30 by 65 Overall 45 Storage 30 by 65 Overall 46 Storage 30 by 65 Overall 47 Storage 30 by 65 Overall 48 Storage	34				Storage	
37 Administration/Technical 50 by 250 93 Storage 40 by 165 38 Administration/Technical 45 by 110 94 Unidentified 40 by 125 39 Administration/Technical 50 by 250 95 IShaped Support 50 by 90 Overall 40 Possible Athletics-Associated 65 by 65 96 Storage 40 by 170 41 Vehicle Maintenance 65 by 67 97 Storage 40 by 170 42 Storage 30 by 60 98 Storage 40 by 65 43 Equipment Storage 45 by 65 99 IShaped Storage 40 by 65 44 Steamplant 40 by 120 (Stack - 80) 100 Storage 20 by 65 Overall 45 Storage 46 by 65 99 IShaped Storage 20 by 65 Overall 46 Storage 47 by 120 (Stack - 80) 100 Storage 20 by 65 Overall 47 Storage 48 Storage 49 by 120 (Stack - 80) 100 Storage 20 by 65 Overall 48 Storage 49 by 120 (Stack - 80) 100 Storage 20 by 65 Overall 49 Storage 10 by 120 (Stack - 80) 100 Storage 20 by 65 Overall 40 Storage 20 by 65 Overall 41 Storage 20 by 65 Overall 42 Storage 30 by 65 Overall 43 Storage 30 by 65 Overall 44 Storage 30 by 65 Overall 45 Storage 30 by 65 Overall 45 Storage 30 by 65 Overall 46 Storage 30 by 65 Overall 47 Storage 30 by 65 Overall 48 Storage 30 by 65 Overall 49 Storage 30 by 65 Overall 40 Storage 30 by 65 Overall 40 Storage 30 by 65 Overall 40 Storage 30 by 65 Overall 41 Storage 30 by 65 Overall 42 Storage 30 by 65 Overall 41 Storage 30 by 65 Overall 42 Storage 30 by 65 Overall 43 Storage 30 by 65 Overall 44 Storage 30 by 65 Overall 45 Storage 30 by 65 Overall 45 Storage 30 by 65 Overall 45 Storage 30 by 65 Overall 46 Storage 30 by 65 Overall 47 Storage 30 by 65 Overall 48 Storage	35			91	Unidentified Facility	
Administration/Technical 50 by 250 93 Storage 40 by 40	36			92	Storage	
Administration/Technical 45 by 110 94 Unidentified 40 by 125	37			93	Storage	
Solution Storage Sto					Unidentified	
40 Possible Athletics-Associated 65 by 65 41 Vehicle Maintenance 65 by 275 42 Storage 40 by 170 42 Storage 40 by 65 43 Equipment Storage 40 by 65 43 Equipment Storage 40 by 65 44 Steamplant 40 by 120 (Stack - 80) 100 Storage 20 by 65 Overall				95	L-Shaped Support	
41 Venicle Maintenance 05 by 275 97 Storage 40 by 65 42 Storage 30 by 60 98 Storage 40 by 65 43 Equipment Storage 45 by 65 99 I-Shaped Storage 20 by 65 Overall 44 Steamplant 40 by 120 (Stack - 80) 100 Storage 20 by 65 Overall				96		
42 Storage 30 by 60 98 Storage 10 by 65 43 Equipment Storage 45 by 65 99 In-Shaped Storage 20 by 65 Overall 44 Steamplant 40 by 120 (Stack - 80) 100 Storage 20 by 65 Overall				97	Storage	
43 Equipment Storage 45 by 65 99 IShaped Storage 20 by 65 Overall 44 Steamplant 40 by 120 (Stack - 80) 100 Storage 20 by 75				98		
44 Steamplant 40 by 120 (Stack - 80) 100 Storage 20 by 75	43				L-Shaped Storage	
4) Storage 25 by 25				100	Storage	
	4-2	otorage	25 DY 25			- •

^{*} All mensuration was performed by CIA/IAS, using scale factors provided by NPIC/TID.

TOP SECRET

<u>25</u>X1

Approved For Release 2005/11/17 : CIA-RDP02T06408R000400010026-8

MAIN SUPPORT AREA AND RAILROAD CLASSIFICATION YARD,

Approved For Release 2005/11/17: CIA-RDP02T06408R000400010026-8

Figure 225X1

<u>2</u>5X1

25X1 _F		TOP SECRET	
L	Approved For Re	elease 2005/11/17: CfA-RDP02T06408R000400010026-8	
25X1	Construction Support Area		
	The Construction Support Area (Figures 22, 23, and Table II) is located midway between Operations Areas A		
25×1	and B and in contained 20 barracks and numerous miscellaneous structures. Between and fine of the larger barracks buildings had		,
	been ruzed. Most of the scattered structures located between barracks area and Doghouse B had been removed by It appears that this area is gradually being	HOUSING AREAS	OPERATIONS AREA A
	abandoned and will eventually probably serve only storage needs.		A.
	Railroad Classification Yard		10
	The railroad classification yard (Figures 20, 21, and		
25X1	Table I), located north of Doghouse A, has undergone no significant changes since The structures within the yard, however, move the more clearly iden-		
20/(1	tified since that time and are shown in Table I.		
	Power Substation		
	The large transformer and switching substitution (Figures 24 and 25), located southwest of the operations areas, is still under construction. Though partially		
25X1	operational, it has undergone considerable development since when a main 220-kv switching yard and a separate 35-kv switching yard were under construction.		
25/1	a separate 35-kv switching yard were under construction. A probable six to ten-kv buried powerline from the latter yard extends into Operations Area B and is the only		
	visible source of external electric power serving the Doghouse operations areas. In late 1966, facilities for		
25X1	a 110-kv switching yard were being installed in the northern coction of the substation, and by six of an anticipated total of 12 circuit breakers had been		
20/(1	omplaced. Although transmission towers are present for two		
	incoming three-phase 220-ky circuits, only one such circuit can be identified entering the substation. Step-		
25X1	down trunsformers were in place on three of the five trunsformer platforms by the remaining two platforms are complete but unoccupied. Also recently		
	installed were powerlines for two, three-phase 110-ky circuits extending southward from the 110-ky yard		
051/4	parallel to the existing 220-kv pawerlines. Observed in and now complete was a probable buried six to ten-kv powerline, originating near the main		
25X1	buried six to tenky powerline, originating near the main entrance to the substation housing area and extending southwestward for over ten miles to a small substition		
	at ABM Launch Complex E-24.		POWER
	Probable Water Treatment Facility	+	
	A large probable water treatment facility (Figure 2) is located approximately 8,500 feet northwest of Doghouse		
	A. Its relationship to the Doghouse complex is unknown at present. It was constructed concurrently with the Doghouse complex and consists of 43 enrith-bunked brains		
	or compartments occupying some 35 acres. Each compartment is 300 feet long and 120 feet wide. Although facilities similar to this are found elsewhere throughout		1
	the Soviet Union, no known operations at the Doghouse complex would appear to require such an extensive treat-	SUBSTATION	~
	ment facility.	The state of the s	

Approved For Release 2005/11/17 : CIA-RDF02T06408R000400010026-8

Figure 2225X1

25Xf

25X1

Approved For Release 2005/11/17/***CIA-RDP02T06408R000400010026-8


TOP SECRET

TABLE II

Structures in the Construction Support Area (Item numbers keyed to Figure 23)

Item	Description	Dimensions (Fcet)*
Trem	Description	Dimensions (ree)
1	Storage	40 by 135
2	Storage	40 by 45
3	Storage	30 by 100
ŭ	Unidentified	15 by 30
5	Steamplant	45 by 70
6	Storage	15 by 45
3 4 5 6 7 8	T-Shaped Messhall	40 by 145, 40 by 70
Ŕ	Unidentified	40 by 145
9	Storage	15 by 45
10-18	Barracks	40 by 145
19	Storage	35 by 135
20	Unidentified	15 by 20
21	F-Shaped Storage	Variable
22	Barracks	30 by 50
23	Barracks	30 by 45
24	Barracks	30 by 45
25	Barracks	30 by 45
26	Barracks	40 by 125
27	Barracks	40 by 125
28	Barracks	40 by 125
29	Barracks	40 by 125
36	Security Guard House	15 by 25
31	Barracks	40 by 145
32	Berracks	40 by 145
33	Barracks	40 by 145
33 3 ¹ 4	Unidentified	15 by 35
35	Unidentified	Undetermined
36	Possible Electric Power-Associated	15 by 30
J.	Structure	-, -0 3-
37-49	Miscellaneous Unidentified Structures,	
0. ,	Probably Unrelated to the Support	
	Area. Most Removed by	
50	Possible Electric Power-Associated	15 by 30

^{*} All mensuration was performed by CIA/IAS, using scale factors provided by NFIC/TID.




TOP SECRET

Figure 23

Approved For Release 2005/11/17 : CIA-RDP02T06408R000400010026-8

Approved For Release 2005/11/17 : CIA-RDP02T06408R000400010026-8

TOP SECRET



NRECTIFIED LINE DRAWING OF POWER SUBSTATION.	NRECTIFIED L	INE DRAWING	OF POWER	SUBSTATION.
--	--------------	-------------	----------	-------------

Fir	ure	24

Item	Description	Dimensions (Fcet)*
1	Control Building with Attached Switching Bay	70 by 100 50 by 255
2	Support Structure	45 by 75
3	Four Oil Storage Tanks	15 Foet Diameter
4	Support Structure	30 by 45 Overall
5	Support Structure	20 by 10
6	Possible Pumping Station	20 by 15
7	Transformer Repair/Servicing Pacility	40 by 45
8	Steumplant	20 by 30
9	Support Structure	40 by 40
10	Support	25 by 95
11.	Barracks	40 by 100
12	Barracks)10 by 100

^{*} All mensuration was performed by CIA/IAS using scale factors provided by NPIC/TID.

TWO 3-PHASE 25X1

Approved For Release 2005/11/17:2CIA-RDP02T06408R000400010026-8

Figure 2525X1 25**X**1

25×1

		TOP SECRET		 02T06408R000400010026-8
	Approved For Release	2005/11/17 : CIA-	RDPO	02106408R000400010026-8
		REFERENCES		
		Documen	t a	
			NPIC.	R-218/64, Suspect AMM Phased Array Radar, Naro Fominsk (Moscow Area), USSR
		9	NPIC.	April 1964 (TOP SECRET R-438/64, Changes at Suspect ADM Phased-Array Radar, Naro Fominsk, USSR,
			NFIC:	February-April 1964, June 1964 (TOP SECRET
		3.	NPIC.	R-918/64, Possible AMM-Associated Activity and Other Installations, Moscow Area, USSR, June-August 1964, November 1964 (TOP SECRET
		4	. NPIC.	Possible AMM-Associated Activity, Moscow Area, USSR,
		_	WDTG.	September 1964-March 1965, August 1965 (TOP SECRET
		,	. NPIC.	Electric Power at Selected AMM and Space Installations, USSR October 1965 (TOP SECRET
		6	. NPIC.	Operational Area B Probable ABM Fhased-Array Radar, Naro Fominsk, USSR, November 1966 (TOP SECRET
		7	. LERCH.	. C.S. <u>Phased Array Radars For Satellite Tracking</u> , November 1961, The Bendix Corporation, Bendix Radio Division (UNCLASSIFIED)
		Requir	ement	
Maps and Charts		c	-RR7-84,40	403
ACIC. US Air Tar	get Chart, Series 200, Sheet 0167-4HL, 2nd edition, 1	March 1963, IAS Pr	oject	
Scale 1:	200,000 (SECRET)	31	0831-7	

Top Secret

Approved For Release 2005/11/17 : CIA-RDP02T06408R000400010026-8

Top Secret