

CLASSIFIED MESSAGE

DATE

~~SECRET~~

ROUTING	
1	9
2	10
3	11
4	12
5	13
6	14
7	15
8	16

rm
Idea
16.12

TO :
FROM :
ACTION:
INFO :
IN: 62974

red
0591-70

TO INFO 25X1A2g CITE

~~SECRET~~ 271945Z CITE [redacted] 4134

PRIORITY 25X1A2g INFO [redacted] 25X1A2g

NO NIGHT ACTION
IDEALIST LOGS MAINT
REF: A. [redacted] 6226
B. [redacted] 3715

TO ADAPT GH311, FABRICATE WOODEN FIVE SIDED BOX (BOTTOM AND FOUR SIDES) WITH SIDE PANELS EXTENDED APPROX 2 INCHES BELOW BOTTOM PANEL. OUTSIDE DIMENSIONS OF BOX TO BE 10.88 BY APPROX 40 INCHES. END PANELS CONTOURED TOP SIDE ON 4.25 RADIUS TO CRADLE THE POD. CENTER OF RADIUS 5.50 ABOVE TOP SURFACE OF BOTTOM PANEL.

SIDE PANELS FIT INSIDE METAL UPRIGHT BOSSES ON GH311 PLATFORM. ADD 1.00 INCH BATTS INSIDE BOTTOM OF BOX TO NEST INSIDE METAL UPRIGHT BOSSES ON GH311 PLATFORM. BOSSES WILL THEN PREVENT SLIPPAGE OF CRADLE.

ASSEMBLE ALL PARTS WITH GLUE AND SCREWS. USE 1.00 INCH PLYWOOD IF AVAILABLE.

~~SECRET~~

GROUP 1 EXCLUDED FROM AUTOMATIC DOWNGRADING AND DECLASSIFICATION

5

25X1A2g

IN: 62574

4134

~~SECRET~~

PAGE-2

ADD FABRIC OR FELT TO CRADLE SURFACES OF END PANELS.

USE LOADING PROCEDURES AS SHOWN IN MI-U2-0120-67, 20 JAN 1967

REVISED 14 MAR 1967.

~~SECRET~~ TOR: 272128Z MAR 67

~~SECRET~~