			0otober 5, 1960
Att:		Dnive Cen	
	ect: #25 MW Dual	Derve beu	
We h	lemon: ave been working mmend the followi	with your	recently and would
	connects the election of the starter, clited valve scatter, clited to tank at this engine on at mount the V-belt bolted to the far cluded is a specificatible hose magnetic starter pushbutton in the	ctric motor and a, Model AGM. lutch take-off, s, positive type nd one spare spen integral fandrive. The end housing for e ial high efficition 208 and 22 e cover.	the 12-1/2 HP Wisconsing This engine includes a speed regulator, Steles walve rotators, interest plug. We will mount and engine base and also agine sub-base will be lenoy muffler and 15 ft. Len-Bradley Bulletin 709 20 volt service, with a
	We also will fur with spare V-bel base arranged for	ts. Engine is	a V-belt drive encleaure mounted on an adjustable and take-up.
	All items above to separately.	will be furnish xeept the start	ned and mounted by ter, which is shipped
	We have been adv	dised that the	standard motor is capable
	volt electrical	either 50 or 60 acures with vol	O cycles and/or 208 or 220 ltage variations of plus

Declassified in Part - Sanitized Copy Approved for Release 2012/09/18: CIA-RDP78-03642A001600040023-5

October 5, 1960

25X1

Re: #25 MW Dual Drive Fan

normal temperature rise under some of these conditions, but it will work satisfactorily as long as the low voltage does not exceed a two-hour per day duration.

This unit will deliver 2400 CFM at 12" SP, when operating at 2900 RPM.

Price of all of the above - - - - - - - 4964.00.

Above price is f.o.b. factory, with railroad freight allowed to freight station nearest destination.

Terms of Sale and Guarantee are on the reverse side of first page of this letter.

If we can be of any further assistance, please do not hesitate to get in touch with us.

. •	Yours very truly,	
CEH: jm		
oc .		

25X1

25X1