

TOP SECRET [Redacted]

OUT 25X1 71280 PRIORITY

TOP SECRET 272150Z NOV 70 CITE [Redacted] 9881

PRIORITY [Redacted]

27 Nov 70 25X1 25X1 03

TAGBOARD

REF: TELECON [Redacted]

25X1 25X1

FOLLOWING INFO AS CONTAINED IN [Redacted] MSG 7229 152241Z OCT 69 IS RETRANSMITTED FOR YOUR GUIDANCE:

QUOTE: SUBJECT: USE OF THE UNIVERSAL GRID AND TITLING INSTRUCTIONS FOR 335A/B PHOTOGRAPHY

1. IT IS REQUESTED THAT [Redacted] ADVISE ALL POTENTIAL USERS, INCLUDING PROCESSING FACILITIES, OF THESE INSTRUCTIONS.

25X1

2. THE "INSTRUCTIONS FOR THE USE OF THE UNIVERSAL GRID WITH 335A/B PHOTOGRAPHY" WILL BE INCLUDED AS AN INTEGRAL PART OF THE HEAD IDENT OF THE ORIGINAL NEGATIVE ON EACH ROLL OF PHOTOGRAPHY IN WHICH THE 335A/B CAMERA SYSTEM IS USED AS THE MISSION SENSOR. THE INSTRUCTION SHOULD BE SPLICED BETWEEN THE HEAD IDENT AND THE FIRST FRAME OF PHOTOGRAPHY ON EACH ROLL, IT SHOULD BE OF SUFFICIENT LENGTH (15 TO 18 INCHES) TO PREVENT THE SPLICE FROM TOUCHING THE NEGATIVE WHEN THE NEGATIVE IS ROLLED ON THE SPOOL. THE INSTRUCTIONS SHOULD BE RIGHT READING WHEN THE TITLING ON THE NEGATIVE IS RIGHT READING.

1

3. INSTRUCTIONS WERE FORMATED AND COPIED AT [Redacted] NEGATIVES AND POSITIVES WERE SENT TO [Redacted] FOR REPRODUCTIONS. [Redacted] WILL FORWARD A SUPPLY TO ALTERNATE PROCESSING FACILITIES ON DIRECTION FROM [Redacted] THE INSTRUCTIONS READ AS FOLLOWS:

25X1 25X1 25X1

"INSTRUCTIONS FOR THE USE OF THE UNIVERSAL GRID 335A/B CAMERA SYSTEM. PLACE THE FILM ON THE LIGHT TABLE SO THAT THE TITLING IS UPRIGHT AND READABLE. PLACE THE GRID OVER THE FILM WITH THE LETTERING AND NUMBERING UPRIGHT AND READABLE. ALIGN X-0 ALONG THE LEFT EDGE OF THE FORMAT. ALIGN Y-0 ALONG THE BOTTOM EDGE OF THE FILM (NOT THE FORMAT). READ AND REPORT COORDINATES IN THE USUAL MANNER, TO THE RIGHT AND UP. EXAMPLE: X-18.0/Y-23.5 INDICATES THE APPROXIMATE POSITION OF THE 24 HOUR CLOCK."

4. THE 335A/B CAMERA SYSTEM ACQUIRES 9 X 9 INCH FORMATS ON INCH WIDE FILM. THERE IS A 0.25 INCH BORDER ALONG EACH EDGE OF FILM.

5. THE ORIGINAL NEGATIVE MUST BE TITLED ON THE EMULSION WITH TEN POINT TYPE. THE TITLING MUST BE PLACED IN THE BORDER CONTAINING THE 24 HOURS CLOCK WITH THE TITLING READABLE WHEN THE CLOCK IS READABLE.

6. THE TITLING WILL INCLUDE:
A. MISSION DESIGNATOR
B. DATE OF PHOTOGRAPHY
C. FRAME NUMBER (FIRST FRAME WILL BE 001 AND ALL FRAMES WILL BE NUMBERED CONSECUTIVELY)
D. K FACTOR (ALTITUDE)
E. CLASSIFICATION

7. THE HEAD AND TAIL IDENTIS WILL INCLUDE:
A. MISSION DESIGNATOR
B. PART IDENTIFER (X OF XX)
C. UNIVERSAL GRID INSTRUCTION FOR 335A/B CAMERA SYSTEM (HEAD IDENT ONLY)
D. CLASSIFICATION
E. HEAD OR TAIL AT EXTREME END OF IDENT.

DISTRIBUTION		
OFFICE	PI	
9.05		
HEAD		
OFFICE SPT.		✓
ADJ. DIR.		
ASST. DIR.		
INSP.		
PLANS.		
TRAINING		
INSTR.		
LABORATORY		
RECORDS		
SECURITY		
ADMIN.		
PERSONNEL		
OTHER		
TOTAL		

1

TOP SECRET

UNQUOTE

GP-1

END OF MESSAGE

ADDRESS BY SANITIZED WITH TEXT

[Redacted] 25X1