

OUT57296

1965 DEC 3 00 03Z

multi

P 022342Z
FM NPIC WASHDC
TO RUCSC/SAC OFFUTT AFB OMAHA NEB
RUCVAA/4080 STRAT WG OL 19 BARKSDALE AFB LA
RUCVAA/2D RTS BARKSDALE AFB LA
RUEKDA/DIA WASHDC
RUECYH/NAVRECONTECHSUPPCEN SUITLAND MD
RUEPIA/CIA WASHDC
RUWBKN/15TH AF MARCH AFB RIVERSIDE CALIF
RUWGAA/2 AF BARKSDALE AFB LA
BT
S E C R E T CITE NPIC 6031.

03 DEC 1965

DISTRIBUTION		
Cy No.	Office	Action
1	File	
	OS	
	ADMIN	
	SEC BR	
	PA & DS	
	CSD	
	IPD	
	PD	
	PSD	
	PSD-ICB	
3, 4	TID	✓
	IAD	
	PAG	
	DIAXX-4	
	SPAD	
	NSA-LO	
	DIA-AP	

15TH AF (FOR DI), SAC (FOR DIM/GOLDEN TREE/DOCR, DM 4) 2D AF (FOR DI)

1. CAMERA B-7 WAS USED IN MISSION 8059 FLOWN ON 30 NOVEMBER 1965. PROCESSING WAS ACCOMPLISHED BY NAV RECON TECH SUPPCEN.

2. ORIGINAL NEGATIVE:

A. EXPOSURE WAS ADEQUATE AND THE RESOLUTION IS GOOD, EXCEPT FOR A FEW SMEARED FRAMES.

B. 9R SIDE: SMALL STATIC DISCHARGE TRACES ARE PRESENT ON BOTH EDGES BUT ARE MORE PROMINENT OUTBOARD. THE INBOARD EDGE CONTAINS ROLLER-INDUCED DISCHARGE TRACES WHICH GRADUALLY DISSIPATE AS THE MISSION PROGRESSES. PLUS AND MINUS DENSITY STREAKS ARE INTERMITTENT THROUGHOUT THE MATERIAL. FRAMES 1615 THRU 1618 ARE DEGRADED BY HEAVY PLUS DENSITY STREAKS AND STATIC TRACES. MANUFACTURER'S SPLICES ARE POSITIONED WITHIN FRAMES 227 AND 1905. FRAME 1589 CONTAINS A BREAKDOWN SPLICE. OTHER BREAKDOWN SPLICES ARE POSITIONED BETWEEN FRAMES 453/454, 782/783, 1501/1502, 1516/1517, 1579/1580, 1692/1693, 2436/2437, 2497/2498, 2927/2928, AND 2960/2961. TWO ROWS OF MINUS DENSITY SPOTS ARE LOCATED 2.45" AND 4.25" FROM THE OUTBOARD EDGE, RESPECTIVELY. THE ON-LINE SPACING BETWEEN SPOTS IS 1.55". A DENSITY GRADIENT IS DETECTABLE IN NUMEROUS FRAMES.

Advance copy
sanitized

Declass Review by NGA

SECRET

-2-

THE TRANSITION LINE IS ORIENTED TO THE MAJOR AXIS OF THE FILM AND VARIES IN LOCATION FROM FRAME-CENTER TO SEVERAL INCHES FROM THE OUTBOARD EDGE OF THE FILM.

C. 9L SIDE: EDGE STATIC ALONG THE OUTBOARD EDGE OCCURS DURING THE FIRST PART OF THE MISSION. MINOR EDGE FOG AND ROLLER CHATTER ARE PRESENT THROUGHOUT THE MISSION. AN INTERMITTENT PLUS DENSITY STREAK BEGINS ON FRAME 1610 AND IS PRESENT THROUGH FRAME 2662. WIDE BANDS OF DIFFERENT DENSITIES ARE VISIBLE ONLY ON FRAMES OF VERY THIN DENSITY. HEAT SPLICES ARE PRESENT THROUGH FRAMES 239, 1604 AND BETWEEN FRAMES 239/240, 967/968, 979/980, 1226/1227, 1612/1613, 1734/1735, 2001/2002. MANUFACTURING SPLICES ARE LOCATED ACROSS FRAMES 967 AND 2931. THE LAST FRAME IS SMEARED AND DOUBLE EXPOSED.

D. THE LAST TITLED FRAME IS 2976.

E. THERE ARE NO MAJOR CAMERA OR PROCESSING MALFUNCTIONS.

3. POSITIVES:

A. THE PI SUITABILITY IS GOOD.

B. THE PRINTING AND PROCESSING WAS GOOD.

C. CLOUDS OBSCURED 25 PERCENT OF THE MISSION.

GP-1

S E C R E T

--END OF MESSAGE--

1