

SECURITY

OUT57948

1966 MAR 12 03 12Z

multi

P 120254Z
 FM NPIC WASHDC
 TO RUEGSC/SAC OFFUTT AFB OMAHA NEB
 RUCVAA/4080 STRAT WG OL 19 BARKSDALE AFB LA
 RUCVAA/2D RTS BARKSDALE AFB LA
 RUEKDA/DIA WASHDC
 RUECYH/NAVRECONTECHSUPPCEN SUITLAND MD
 RUEPIA/CIA WASHDC
 RUWBKN/15TH AF MARCH AFB RIVERSIDE CALIF
 RUWGAA/2 AF BARKSDALE AFB LA
 BT
 S E C R E T CITE NPIC 6654.

15TH AF (FOR DI), SAC (FOR DIM/GOLDEN TREE/DOCR, DM 4) 2D AF (FOR DI).

1. CAMERA B 7 WAS USED IN MISSION 8076 FLOWN ON 10 MARCH 1966,
 14 MAR 1966
 PROCESSING WAS ACCOMPLISHED BY NAV RECON TECH SUPPCEN.

2. ORIGINAL NEGATIVE:

A. EXPOSURE WAS ADEQUATE AND RESOLUTION IS FROM FAIR TO GOOD!
 THE FAIR RATING IS BECAUSE OF SMEAR CAUSED BY VEHICLE MANEUVERS.

B. 9R SIDE: MINOR ROLLER CHATTER IS PRESENT ALONG BOTH EDGES
 THROUGHOUT THE MISSION. MINOR EDGE STATIC OCCURS INTERMITTENTLY
 ALONG THE OUTBOARD EDGE. FOGGED STREAKS, ENTER THE FORMAT FROM *3,45*
 THE OUTBOARD EDGE, RUN DIAGONALLY FOR 2.0" TOWARD THE TAKE-UP ENDS
 OF FRAMES 1450, 1666, 1728, 1738 AND 1893. A HEAT SPLICE IS PRESENT
 THROUGH FRAME 1275 AND A MANUFACTURING SPLICE THROUGH FRAME 1154.

C. 9L SIDE: EDGE STATIC IS PRESENT ALONG BOTH EDGES OF THE
 FILM THROUGHOUT THE MISSION. ROLLER CHATTER IS INTERMITTENTLY
 PRESENT ALONG THE INBOARD EDGE. THERE ARE TWO ROWS OF MINUS DENSITY
 DOTS ALONG THE INBOARD EDGE OF THE FILM. THEY ARE BOTH 1.5"
 APART BUT 0.8" AND 1.7" FROM THE INBOARD EDGE. THE ROW 0.8"

7	
Action	

SECRET

-2-

FROM THE EDGE IS ONLY VISIBLE FOR APPROXIMATELY THE FIRST 200 FRAMES. THE ROW THAT IS 1.7" FROM THE EDGE IS INTERMITTENTLY DETECTABLE THROUGHOUT THE MISSION. THERE IS A SPLASH-TYPE LIGHT LEAK ALONG THE OUTBOARD EDGE OF FRAMES 655, 729 AND 886. HEAT SPLICES ARE PRESENT IN FRAME 1289 AND BETWEEN FRAMES 1602/1603 AND 1625/1626. A MANUFACTURING SPLICE IS LOCATED IN FRAME 1468.

D. STARTING AT FRAME 308 THE CAMERA REMAINED IN THE 1L POSITION AND CONTINUED THIS WAY THROUGHOUT THE MISSION. THE LAST TITLED FRAME IS 2596.

E. A CAMERA MALFUNCTION RESULTED IN ONLY THE 1L POSITION BEING RECORDED IN FRAMES 308 THRU 2596. THERE WERE NO PROCESSING MALFUNCTIONS.

3. POSITIVE:

A. PI SUITABILITY IS FAIR TO GOOD.

B. PRINTING AND PROCESSING WAS GOOD.

C. CLOUDS OBSCURED OR DEGRADED APPROXIMATELY 15 PERCENT OF THE MISSION.

GP-1

S E C R E T

--END OF MESSAGE--

1