

CONFIDENTIAL

-2-

Classes 1,2 and 3 of the A and B types were 2.7 meters long. Classes 4 and 5 of the A and B type were 2.5 meters long.

Rails

50X1

3. Three types of rails were used on the line as follows:

<u>type</u>	<u>kg/m</u>	<u>height</u>	<u>width of base</u>	<u>width of head</u>
1-A	42.98	140 mm	125 mm	70 mm
2-A	38.28	135 mm	114 mm	68 mm
3-A	32.69	127 mm	110 mm	60 mm

Types 1-A and 2-A were used on the main lines for both single and double track. Type 3-A was used on secondary lines and sidings. There was an obsolete type known as 4-A (not manufactured since 1917) that was very light and could be found on a few sidings. All types of rails were divided into two sizes; those 12.8 meters long and those 10.67 meters long. The life of a rail averaged between 30 and 40 years on the main and secondary lines. Rails removed from main and secondary lines were usually used on sidings, if at all **serviceable**. Re-rolled rails were not used. Replacements on double-track main lines usually were between six and eight rails annually; on secondary, single-track lines between two and four rails annually. Rails on sidings were very seldom replaced.

Fuel and Electric Power

4. The most common type of locomotive used on the Kiev-Fastov run was the "ShCh", which, with tender, weighed between 65 and 75 mts. The average load hauled on this run (loaded freight train without locomotive and tender) was about 1500 metric tons. The trip took (one way) about two hours at the technical speed of 30 km per hour. Coal consumed for a one way trip averaged between four and five tons. To make the same trip, an "M" type (passenger) locomotive with tender (60 to 70 mt) plus 800 mt load, took about 80 minutes and consumed between three and four tons of coal. Loaded cars were never weighed in the Soviet. The gross weight was determined on the basis of an assumed average, per loaded and empty car. I am unable to give any averages for switching locomotives.
5. Coal locomotives only were used on the Kiev-Fastov line. The freight locomotive, type "ShCh", used between 60 and 90 kgs of coal per locomotive-kilometer. The most common passenger locomotive was the "M" type which used between 50 and 75 kgs of coal per locomotive-kilometer. In 1940 there were around 48 pairs of trains a day on this line (by pairs I mean 48 trains from Kiev to Fastov and 48 from Fastov to Kiev, a total of 96 in both directions. A locomotive leaving Kiev would pull one train to Fastov and then return to Kiev with another train). Of this total, about 30% were passenger trains. The station at Kiev (which included the stations Kiev I, Kiev II, Darnitsa and other sub-stations in Kiev) required about 2000 to 2250 mts of coal daily. About 75% of this coal was consumed by locomotives (figuring about 100 locomotives daily leaving Kiev in all directions). The remaining 25% was used for repair facilities, stations, etc. I am unable to furnish consumption figures per unit repaired.

MANPOWER

6. The Kiev-Fastov line as such had a total of about 1000 workers of all types. Kiev was a major railroad center and the main administration offices of the South-West Railroad system were located there. Including

CONFIDENTIAL

CONFIDENTIAL

-3-

all sub-stations, the following number of workers were employed:

<u>Department</u>	<u>Average number of workers</u>	
Track Service (line maintenance, repair teams, etc.)	1000	50X1
Rolling stock repair facilities	3000	
Transport service (locomotive engineers and crews)	2000	
Traffic service (switchers, conductors, brakemen, etc)	5000	
Commercial service (loaders, etc)	1000	
Communications (telegraph, telephone etc)	500	
Administration service	1000	
Railroad technical schools (900 to 1200)	1000	
Main Administration of SWRR System	5000	
	<u>19,500</u>	

(1000 workers directly connected with the Kiev-Fastov Division included).

A passenger train on a short run had

1-chief conductor
 3 or 4-assistant conductors
 1-locomotive engineer
 1-assistant engineer
 1-stoker

 7 or 8 average

(A long distance passenger train also had one porter assigned to each car - usually 12. These porters were assigned for the complete trip and were not replaced at intermediate stations)

A freight train crew was made up as follows:

1-engineer
 1-assistant engineer
 1-stoker
 2-conductors
 4-brakemen
 1-oiler

 10

7. The average capital repair job of a locomotive required up to 25,000 man hours. A medium repair job (annual) required up to 5000 man hours. Capital repair of a car (passenger or freight) required up to 10,000 man hours. The washing of a locomotive boiler took about 48 man hours. The average work week was between 42 and 48 hours per week.

Rolling Stock

8. The average life of a locomotive was estimated at 40 to 50 years, freight cars 10 to 15 years and passenger cars from 20 to 25 years. A capital repair job was made every five years on locomotives and every four years on cars (freight and passenger). Medium or annual repairs were made on locomotives and cars every year. Minor repair (overall inspections) to locomotives were made every month. The following length of time was consumed as an average for locomotive and car repairs:

CONFIDENTIAL

CONFIDENTIAL
-4-



<u>Capital repair</u>	<u>Annual repair</u>	<u>Current repairs</u>	
Locomotives 1 to 2 months	10 to 15 days	1 to 3 days	
Cars 1 month	5 to 10 days	1 to 3 days	50X1

I am unable to furnish any figures on the consumption of materials used for various repairs.

-end-

LIBRARY SUBJECT & AREA CODES

755.224	234N
755.223	234N
755.35	234N
755.61	234N
755.34	234N

CONFIDENTIAL