

GINEV, B.; MURDZHEV, A.

Emergency surgical aid in closed abdominal injuries. Khirurgia  
15 no.9/10:924-927 '62.

1. Iz Katedrata po fakultetska khirurgia s urologia pri  
VMI [Vissh meditsinski institut] "I.P. Pavlov" - Plovdiv.  
(ABDOMINAL INJURIES) (EMERGENCIES)

GINEV, Boiu; ZUNZOV, Ivan

Biochemical and electrophysiological changes in commotio cerebri. Khirurgia 15 no.9/10:856-858 '62.

1. Iz Katedrata po fakultetska khirurgia s urologia pri VMI [Vissh meditsinski institut] "I.P. Pavlov" - Plovdiv.  
(BRAIN INJURY ACUTE)

KHAIDUDOV, L., prof.; ARMENKOV, At.; PANTEVA, L.; GINEV, B.

Combined injuries of the abdomen and pelvis. Khirurgia 15  
no.9/10:839-847 '62.

(ABDOMINAL INJURIES) (PELVIS)

GINEV, B.; MISHEV, P.

On tuberculous disorders of the urogenital system. Khirurgia  
15 no.11:1022-1024. '62.

1. Iz Katedrata po fakultetska khirurgia s urologia pri  
VMI [Vissh meditsinski institut] "I.P. Pavlov - Plovdiv.  
(TUBERCULOSIS UROGENITAL)

DEYFNICHIN, P. (Bolgariya, g.Plovdiv, ul. Bratan Shukerov, d.29); GINEV, B.;  
SHCHEREV, A.

Precancerous diseases of the stomach. Vop. onk. 9 no.11:  
31-37 '63. (MIRA 18:2)

1. Iz kafedry fakul'tetskoy khirurgii (rukovoditel' - dotsent  
Ya. Dobrev) Vysshego meditsinskogo instituta imeni Pavlova,  
Plovdiv, Bolgariya.

GINEV, B.

Chronic invagination of the large intestine. Khirurgia 16  
no.1:77-79 '63.

1. Iz Katedrata po fakultetska khirurgia pri VMI [Vissh  
meditsinski institut] "I.P. Pavlov" - Plovdiv.  
(INTUSSUSCEPTION) (INTESTINE LARGE)

GINEV, B.

Total renal rupture in closed abdominal injury. Khirurgiia  
(Sofiiia) 16 no.9:878-880 '63.

1. Iz Katedrata po fakultetska khirurgiia pri VMI "I.P.Pavlov",  
Ploddiv.

GINEV, B.; ZANZOV, I.

Clinical value of capillaroscopy in some surgical diseases. Folia  
med. (Plovdiv) 6 no.1:33-36 '64

1. Hohes medizinisches Institut "I.P.Pavlov" zu Plovdiv, Bulgarien,  
Lehrstuhl für fakultätschirurgie und urologie (Vorstand: Kand.  
der med. Wissenschaft Prof. J.Dobrev).



GINEV, B.; ZUNZOV, Iv.

On functional changes in the cardiovascular system and neutral 17-ketosteroids during extensive surgical interventions. Khirurgiia (Sofia) 18 no.3:351-357 '65.

1. VMI, Plovdiv, Katadra po fakultetska khirurgiia (rukovoditel: prof. IA. Dobrev).

GINEV, B.

A case of congenital anomaly of the peritoneum. *Khirurgia*  
(Sofia) 18 no.4:499-500 '65.

1. Katedra po fakultetska khirurgia s urologia, Vissh  
meditsinski institut, Plovdiv (rukoveditel - prof. Ia Dobrev).

PLOSKOV, D.; ANDREEV, T.; BELMER, Iu.; GINDEL, I.; KALEV, N.; KIM, G.; KIM, C. M.;  
LI, C.S.; LI, Z.I.; PETROV, N.; SIMBONOV, L.

Etio-pathogenetic surgical treatment of torpid infections with various  
localizations in the light of I. P. Pavlov's theory. *Khirurgia, Sofia*  
11 no.1:23-27; contd. 1958.

(INFECTIONS, surg.  
torpid infect. (Bul))

PLOSKOV, D.; ANDREEV, T.; BELMER, IU.; GINEV, I.; KALEV, N.; KIM DZHUN, KIM  
CHE M'ON.; LI CHAN SO.; LI ZON I.; PESTROV, P.; SIMONOV, L.

Etiopathogenetic surgical treatment of torpid infection with various  
localizations in the light of I. P. Pavlov's teaching. Khirurgia,  
Sofia 11 no.3:207-215 Mar 58.

(INFECTION, surg.

in torpid infect. in various localizations (Bul))

BELOSLUDTSEVA, Ye.I.; GINEVICH, G.I.

Continuous vapor-phase dehydrogenation of borneols to camphor and  
the layout of equipment for it. *Gidroliz.i lesokhim.prom.* 12 no.3:  
15-17 '59. (MIRA 12:6)

1. Novosibirskiy khimicheskiy zavod.  
(Borneol) (Camphor) (Dehydrogenation)

S/184/61/000/005/008/009  
D041/D113

AUTHORS: Ginevich, G.I.; Artem'yeva, L.A., Engineers.

TITLE: New apparatus for vaporizing and mixing liquid organic compounds

PERIODICAL: Khimicheskoye mashinostroyeniye, no. 5, 1961, 45-46

TEXT: The article contains a detailed description of the design and operation of a new apparatus (Fig. 2) for mixing and vaporizing liquid organic compounds for which G.I. Ginevich, P.A. Artem'yeva and Ya. A. Tsapnik have obtained the author's certificate no. 129899 dated October 21, 1959. The apparatus is based on the layer-evaporation principle and replaces the bubble-type evaporator which has larger dimensions and is less efficient. There are 2 figures. ✓

Card 1/3

New apparatus for ...

S/184/61/000/005/008/009  
DO41/D113

Legend: 1 -- body of the apparatus; 2 -- body of the mixer; 3 -- sleeve containing the thermo-couple; 4 -- steam cushioning appliance; 5 -- mixing chamber; 6 -- protruded tube; 7 -- protruded tube; 8 -- electric valve; 9 -- pneumatic slide valve; 10 -- charging boxes; 11 -- containers; 12 -- tube; 13 -- tube; 14 -- tube; 15 -- protruded tube; 16 -- protruded tube; 17 -- diaphragm; 18 -- flow meter; 19 -- pneumatic valve; 20 -- differential pressure meter; 21 -- protruded tube; 22 -- vacuum gage; 23 -- control panel; 24 -- protruded tube; 25 -- secondary device; 26 -- secondary device; 27 -- protruded tube; 28 -- protruded tube; 29 -- differential pressure meter; 30 -- pipe; 31 -- pneumatic slide valve; 32 -- diaphragm. 33 -- exhaust gases from the adsorption columns; 34 -- to the vacuum pump; 35 -- alcohol; 36 -- air. ✓

Card 3/3

GINEVICH, G.I.; PREOBRAZHENSKIY, V.N.; SPIRIN, V.V.

Continuous unit for milling aminoplastics. Plast.massy no.11:  
58-59 '61. (MIRA 14:10)  
(Aminoplastics) (Milling machinery)



GINEVICH, G.I.

Redesigning the absorption system of a formalin plant. Khim.prom.  
no.8:710 D '59. (MIRA 13:6)

1. Novosibirskiy khimicheskiy zavod.  
(Formaldehyde) (Plate towers)

GINEVICH, G.I.

Electric furnace for curing performs of fluorplast-4. Plast.  
massy no.4:45-46 '61. (MIRA 14:4)  
(Plastics industry—Equipment and supplies)

GINEVICH, G.I.; SKUE, G.I.; SHCHUGAREV, V.T.

Studying the process of continuous distilling-off of highly  
volatile substances in the production of plasticizers from  
dibutylphthalate and dioctylphthalate. Plast.massy no.3:64-  
67 '64. (MIRA 17:3)

NAKROKHIN, B.G.; SHIBANOV, G.V.; GINEVICH, G.I.; OBRAZTSOV, A.I.;  
MATROS, Yu.Sh.; SKUE, G.I.; NAKROKHIN, V.B.; ITENBERG, Sh.M.;  
RASHRAGOVICH, Kh.D.

Oxidation of methanol to formaldehyde on oxide catalysts.  
Khim. prom. 41 no.2:17-19 F '65. (MIRA 18:4)

CHEKIN, V.F.; GINEVSKAYA, I.A.

Modernization of eye instruments. Vest. oft. 73 no. 3:53-54 My-Je  
'60. (MIRA 14:1)  
(EYE, INSTRUMENTS AND APPARATUS FOR)

GINEVSKIY, A.; KAREPENKO, I.; FEDOROVIC, N.

Deliveries made by the Department of Technical Control  
must be of high quality. Podn org 18 no. 3:140 Mr '64.

GINEVSKIY, A.S. (Moskva)

Energy characteristics of presonic diffuser conduits. Izv.AN SSSR Otd.tekh.  
nauk no.3:152-154 Mr '56. (MIRA 9:7)  
(Gas flow) (Pipe--Hydrodynamics)

PHASE I BOOK EXPLOITATION

SOV/6580

Solodkin, Yefim Yefremovich, and Aron Semenovich Ginevskiy

Turbulentnoye techeniye vyazkoy zhidkosti v nachal'nykh uchastkakh  
osesimmetrichnykh i ploskikh kanalov (Turbulent Flow of Viscous  
Fluid in Inlet Sections of Axisymmetric and Plane Channels)  
Moscow, Oborongiz, 1957. 55 p. (Series: Moscow.  
Tsentral'nyy aero-gidrodinamicheskiy institut. Trudy, no. 701)  
No. of copies printed not given.

Ed.: Yu. G. Zakharov, Candidate of Technical Sciences; Ed. of  
Publishing House: L. I. Sheynfayn; Tech. Ed.: N. A.  
Fukhlikova; Managing Ed.: Ye. V. Latynin, Engineer.

PURPOSE: This book is intended for technical personnel concerned  
with fluid flow.

COVERAGE: The book discusses the flow of viscous fluid in the  
inlet section of ducts of various cross sections. In the case  
of axisymmetrical duct, it is shown that a better agreement  
is obtained between the calculated and the experimental results

Card 1/3



Turbulent Flow of Viscous (Cont.)

SOV/6580

by taking into account the transverse curvature of the surface than by employing the usual theories based on the power or logarithmic law of velocity distribution in the boundary layer. However, in the case of a plane duct, good agreement between the calculation and the experiment is obtained using the logarithmic law of velocity distribution. The characteristics of a circular tube and a plane duct can be considered as extreme cases of an annular cross-section duct. No personalities are mentioned. Three Soviet and three German references are found in the text.

TABLE OF CONTENTS:

Ch I.	Turbulent Boundary Layer and Resistance in the Inlet Section of an Axisymmetrical Divergent Duct with Zero-Pressure Gradient	3
Ch II.	Turbulent Boundary Layer and Resistance in the Inlet Section of a Circular Duct	26

Card 2/3

AMZ016094

BOOK EXPLOITATION

S/0795

Solodkin, Yefim Yefremovich; Ginevskiy, Aron Semenovich

Turbulent flow of a viscous fluid in the initial sections of axially symmetric and plane channels (Turbulentnoye techeniye vyazkoy zhidkosti v nachal'nykh uchastkakh osesimmetrichnykh i ploskikh kanalov) Moscow, Oborongiz, 1957. 55 p. illus. No. of copies not given. Editor: Zakharov, Yu. G. (Candidate of Technical Sciences); Deputy editor: Letyagin, Ye. V. (Engineer); Publishing house editor: Sheynfayn, L. I.; Technical editor: Pukhlikova, N. A.

Series note: Moscow. Tsentral'nyy aero-gidrodinamicheskiy institut. Trudy\*, no. 701

TOPIC TAGS: turbulent flow, viscous fluid, initial section, axially symmetric channel, flat channel, velocity distribution, circular pipe, turbulent boundary layer, drag

PURPOSE AND COVERAGE: The flow of a viscous fluid in the initial section of channels of various cross section is analyzed in this brochure. It is shown that

Card 1/3

AM4016094

consideration of the cross-sectional curvature of the surface in the case of an axially symmetric channel will give better agreement between experimental and calculated characteristics than the usual theories utilizing exponential or logarithmic laws of velocity distribution in the boundary layer. In the case of the flat channel, the logarithmic law will provide good agreement between calculated and experimental data. The characteristics of a circular pipe and a flat channel can be analyzed as limit cases of a channel of annular cross section.

TABLE OF CONTENTS:

- I. Turbulent boundary layer and drag of the initial section of an axially symmetric expanding channel with a zero pressure gradient -- 3
- II. Turbulent boundary layer and drag of the initial section of a circular pipe -- 26
- III. Turbulent boundary layer and drag of the initial section of a flat channel -- 41

Card 2/3

СИЛСВСКІЯ А. С.

Distr: 4E4f/4F1

A METHOD FOR COMPUTING THE TURBULENCE  
IN A BOUNDARY LAYER WITH A

NAL PRESSURE GRADIENT IS PRESENT P. K.

С. С. СИЛСВСКІЯ И А. С. СИЛСВСКІЯ

Вопросы Аэродинамики, 1957, № 1, с. 1-10

Вопросы Аэродинамики, 1957, № 1, с. 1-10

It can be used for determining the values of the

friction coefficient and the velocity profile

as a result of a first approximation. The numerical

representations of the resistance law and the velocity

profile are compared with experimental data.

The effect of a significant increase in the friction coefficient

can possibly occur. It is shown that the theory and

experiment are in a satisfactory agreement.

SOLODKIN, Ye.Ye., kand.tekhn.nauk; GINEVSKIY, A.S.

Determining characteristics of the turbulent boundary layer  
and the resistance of long axisymmetric bodies. Trudy NTO  
sud.prom. 7 no.2:81-106 '57. (MIRA 12:1)  
(Stability of ships)

SOV/124-58-11-12695

Translation from: Referativnyy zhurnal, Mekhanika, 1958, Nr 11, p 109 (USSR)

AUTHOR: Ginevskiy, A. S.

TITLE: Influence of the Viscosity of a Fluid on the Intensity of the Circulation About a Fluid Foil in a Hydrodynamic Cascade (Vliyaniye vyazkosti zhidkosti na velichinu tsirkulyatsii vokrug profilya gidrodinami-cheskoy reshetki)

PERIODICAL: V sb.: Prom. aerodinamika. Nr 9, Moscow, Oborongiz, 1957, pp 5-15

ABSTRACT: An investigation of the dependence on the fundamental geometric parameters of a plane cascade of the ratio  $k_{\Gamma} = \Gamma / \Gamma_{id}$ , i. e., the ratio of the circulation about a cascade foil of a viscous incompressible fluid flow and the corresponding circulation of an ideal fluid. It is assumed that the fluid foil differs only little from straight segments. Equating to zero the total vorticity of the flow downstream of the cascade is tantamount to equating the velocities at the outer boundary of the boundary layer shedding from the fluid foil. Applying this condition to the flow of an ideal fluid through a cascade of foils, the author obtains (with an accuracy up to the terms of  $\delta^2$  order)

Card 1/2

Influence of the Viscosity of a Fluid on the Intensity of the Circulation (cont.) SOV/124-58-11-12695

$$k_{\Gamma} = 1 - k \sqrt{\bar{\delta}_V \bar{\delta}_N}$$

where  $k$  is a function of the solidity ratio and escape losses of the cascade, and  $\bar{\delta}_V$  and  $\bar{\delta}_N$  are the nondimensional thicknesses of the boundary layers shedding from the upper and lower sides of the foil, respectively. The calculated values of  $k_{\Gamma}$  tend toward unity as the solidity ratio increases and the angle of escape decreases. Using experimental data for compressor cascades consisting of solid fluid foils with a shockfree entry, the author obtains  $k_{\Gamma} = 0.86-0.93$ . The results of the investigation, on the whole, bear a qualitative character.

L. G. Naumova

Card 2/2

PA - 2127

**AUTHOR:** FEDYAYEVSKIY, K.K., GINEVSKIY, A.S.

**TITLE:** The Computation Method of a Turbulent Boundary Layer in the Case of the Existence of a Transverse Pressure Gradient (Metod rascheta turbulentnogo pogranichnogo sloya pri nalichii prodol'nogo gradyenta davleniya. Russian).

**PERIODICAL:** Zhurnal Tekhn. Fiz., 1957, Vol 27, Nr 2, pp 309 - 326 (U.S.S.R.)  
Received: 3 / 1957      Reviewed: 4 / 1957

**ABSTRACT:** A simple approximated method for the computation of the characteristics of a turbulent boundary layer is described. For the purpose of a simplification of the equations for the velocity profile and the law of resistance not  $\tau$ , but  $\sqrt{\tau}$  is represented as a polynomial according to y-powers. At first the velocity profile is derived in a turbulent boundary layer. Next, the formula for the law of resistance is derived and reduced to a form suited for computation. The significance of the constants  $\kappa$  and  $\alpha$  is mentioned. Both are experimentally determined. For practical purposes  $\kappa = 0.4$  and  $\alpha = 11.5$  can be assumed. A diagram represents the law of resistance. In the next chapter the impulse equations are integrated and it is shown on this basis in what manner the location of the point in which the liberation of the turbulent boundary layer takes place is determined. Computed and experimental results were compared and were found to be in good agreement. The computation method of the characteristics of the twodimensional turbulent boundary layer with essential transverse cross gradients of pressure is distinguished

Card 1/2



The Computation Method of a Turbulent Boundary layer in the Case  
of the Existence of a Transverse Pressure Gradient. PA - 2127

by a sufficient operation capacity and makes it possible already  
in first approximation, to determine the conditional thickness of the  
layer as well as the value of the local friction coefficient and the  
location of the point at which liberation takes place. The graphical  
representation of the law of resistance obtained shows the possi-  
bility of the occurrence of special states accompanied by a con-  
siderable reduction of the local friction coefficient. From this it  
follows immediately that at certain relations and in the case of a po-  
sitive cross gradient of pressure conditions are created which  
lead to the liberation of the turbulent boundary layer. (11 illu s-  
trations and 2 tables)

ASSOCIATION: Not given

PRESENTED BY:

SUBMITTED: 25.4.1956

AVAILABLE: Library of Congress.

Card 2/2

SOV/124-58-8-8889

Translation from: Referativnyy zhurnal, Mekhanika, 1958, Nr 8, p 80 (USSR)

AUTHORS: Solodkin, Ye.Ye., Ginevskiy, A.S.

TITLE: The Turbulent Flow of a Viscous Fluid in the Inlet Portion of Axisymmetric and Plane Channels (Turbulentnoye techeniye vyazkoy zhidkosti v nachal'nykh uchastkakh osesimmetrichnykh i ploskikh kanalov)

PERIODICAL: Tr. Tsentr. aero-gidrodinam. in-ta, 1957, Nr 701, 57 pp, ill.

ABSTRACT: An approximate solution is offered for the problem of the turbulent boundary layer and resistance in the inlet portion of: 1) An axisymmetric divergent channel having a zero pressure gradient, 2) a circular conduit, and 3) a plane channel. Attention is given herein to the matter of the influence exerted by the transverse curvature of the channel surface on the velocity profile, the local friction coefficient, and on the other characteristics of the turbulent boundary layer. The authors considered that in the channel's inlet section the velocity is constant and that the static pressure across the width of the boundary layer does not vary. Analysis of the differential

Card 1/4

SOV/124-58-8-8889

## The Turbulent Flow of a Viscous Fluid (cont.)

equations describing the mean stationary flow in the channel's turbulent boundary layer revealed that near the surface (correct up to the terms of the third order) the tangential-stress distribution across the width of the layer obeys the condition  $r \tau = \text{const} = r_0 \tau_0$ . Here  $r$  is the radius of a fluid element in the boundary layer,  $r_0$  is the radius of the channel cross section,  $\tau$  is the frictional stress in the boundary layer, and  $\tau_0$  is the frictional stress at the channel surface. Taken together with the Prandtl relationship  $\tau = \rho l^2 (\partial u / \partial y)^2$ , [wherein  $\rho$  is the density of the liquid,  $l$  the turbulent mixing length, and  $\partial u / \partial y$  the mean-flow-velocity gradient normal to the channel wall], this permits the evolution of a formula for the velocity profile in the turbulent boundary layer of an axisymmetric channel. When  $r_0 \rightarrow \infty$ , the formula reverts to the well-known logarithmic velocity profile of the turbulent layer of a plate. In the immediate vicinity of the channel wall the velocity distribution is arrived at on the basis of the hypothesis which posits the existence of a laminar sublayer in which  $\tau = \mu \partial u / \partial y$  ( $\mu$  being the viscosity coefficient of the liquid). The resistance law is obtained by equating the two velocity distributions at the boundary of the laminar sublayer. The thickness of the laminar sublayer is determined from the usual relationship,  $\delta^0 = \alpha_1 \nu / v_*$ , wherein  $\nu = \mu / \rho$ . The calculations were

Card 2/4

SOV/124-58-8-8889

The Turbulent Flow of a Viscous Fluid (cont.)

performed on the assumption that the turbulence constants  $k_1$  and  $a_1$  maintain values equaling the corresponding values for the case of a plate, namely,  $k_1=0.392$  and  $a_1=11.5$ . As a result of integration of the impulse equation, a determination is made, for different values of the Reynolds number, of the aerodynamic characteristics of an axisymmetric divergent channel having a zero pressure gradient, and an analysis is performed of the influence exerted by the transverse curvature of a concave surface on the characteristics of the boundary layer. It is demonstrated that because of the curvature of the surface the velocity profile becomes less bulgy, which circumstance reduces correspondingly the coefficient of frictional resistance (as compared with cases in which the channel is a flat surface). Moreover, the influence exerted by a transverse curvature of the surface becomes especially significant when the ratio  $\delta/r_0$  approaches unity. The data obtained are used to solve next the problem relating to the inlet portion of a circular conduit. Here the influence exerted by the longitudinal pressure gradient is taken into account only in the impulse equation. By solving the problem the authors arrive at the aerodynamic characteristics of the inlet portion of a circular conduit, including the length of the inlet portion for different values of the Reynolds number. When determined by this means, the length of a circular conduit's inlet portion exceeds by a factor of approximately three

Card 3/4

SOV/124-58-8-8889

The Turbulent Flow of a Viscous Fluid (cont.)

its length as calculated from the velocity power profile (as per the Lattsko theory), and exceeds by a factor of two its length as calculated with a logarithmic velocity profile (as per the Shablevskiy theory), but it does approximate very closely the length obtained experimentally (by Kirsten). In conclusion the aerodynamic characteristics are calculated for the inlet portion of a plane channel for a logarithmic velocity distribution in the boundary layer. Inasmuch as a circular conduit and a plane conduit represent two limiting cases of an annular-section conduit, the relationship found to exist between the aerodynamic characteristics and the length of either type of channel is depicted for both cases on a single graph. It is shown that, if a channel's hydraulic radius is taken as its characteristic linear dimension, the stated relationships will be virtually the same in the two cases, i.e., in that of a plane and in that of a circular conduit, and that they may therefore be employed to determine the characteristics of the inlet portion of an annular-section conduit.

V.I. Yagodkin

Card 4/4

DOVZHUK, Samuil Aronovich; GINEVSKIY, A.S., kand.tekhn.nauk,red.; SHEYNFAYN, L.I.,  
izdatel'skiy red.; YEVSTIGNEYEVA, M.N., tekhn.red.

[Designing blades of subsonic axial-flow compressors] Profilirovanie  
lopatok oseвого dozvukovogo kompressora. Moskva, Oborongiz, 1958.  
138p. (Promyshlennaya aerodinamika No.11) (MIRA 11:12)  
(Compressors--Blades) (Aerodynamics)

GINEVSKIY, A.S.

YUDIN, Yevgeniy Yakovlevich; GINEVSKIY, A.S., kand.tekhn.nauk, red;  
SHEYNFAYN, L.I., izdatel'skiy red.; ZUDAKIN, I.M., tekhn.red.

[Investigation of noises in ventilation installations and methods  
for preventing them] Issledovanie shuma ventilatornykh ustanovok i  
metodov bor'by s nim. Moskva, Gos. izd-vo obr. promyshl., 1958.  
227 p. (Moscow, Tsentral'nyi aero-gidrodinamicheskii institut.  
Trudy, no.713). (MIRA 11:4)  
(Ventilation) (Acoustical engineering)

GINEVSKIY, A.S.

Investigating two systems for changing blading areas in axial-flow compressor stages. Prom. aerodin. no.10:61-76 '58.

(MIRA 11:8)

(Compressors)



GINEVSKIY, A.S.; SOLODKIN, Ye.Ye. (Moskva)

Effect of lateral surface curvature on the characteristics of  
the axisymmetric turbulent boundary layer. Prikl.mat. i mekh.  
22 no.6:819-825 N-D '58. (MIRA 11:12)  
(Boundary layer)

G. N. E. U. S. K. I. Y., A. S.

PLATE I BOOK EXTRACTS 507/3695

1A(1)

Central'nyy aero-gidrodinamicheskiy Institut  
Ventilyatsionnyy i vyzhivoprovody (Ventilators and Air Ducts) Moscow, Obozreniye,  
1959. 249 p. (Series: Prikladnaya aerodinamika, sbornik No. 12)  
Number of copies printed not given.

Ed. (Title page): K.A. Unakov, Professor; Ed. (Inside book): A.S. Giverniy,  
Candidate of Technical Sciences; Ed. of Publishing House: I.A. Shchukina  
Tech. Ed.: I.M. Dubakina; Managing Ed.: A.S. Zayarnitskaya, Engineer.

PURPOSE: This book is intended for engineers, technicians and scientific workers  
specializing in the field of industrial aerodynamics and ventilation.

CONTENTS: This collection of 11 articles deals with problems of ventilation  
technology. Results of experimental and theoretical investigations for the  
aerodynamic characteristics of axial and centrifugal fans are described.  
Some designs of new, highly economical centrifugal fans are described and  
the drag coefficients of various ducts and elements of ventilation systems  
are given. No personalities are mentioned. References follow most articles.

6. Kuznetsov, V.K. and K.V. Chubrykova Regulation of Centrifugal Fans With  
Flat Guide Vanes 70  
This article presents experimental materials on regulating centrifugal fans by  
the use of flat guide vanes.  
The author describes the design of fan model Tsk-70 with flat inclined  
blades developed by TAOI. This fan has good aerodynamic characteristics and  
is now mass-produced as a general purpose fan. Comparative results of tests  
are given.

7. Chepyzhina, M.Y. Centrifugal Fan Volume Regulation by Changing the Passage 110  
Section of the Inlet or the Body  
The author describes the design of fan model Tsk-70 with flat inclined  
blades developed by TAOI. This fan has good aerodynamic characteristics and  
is now mass-produced as a general purpose fan. Comparative results of tests  
are given.

8. Pankov, A.G., I.L. Lokhin, and P.O. Mamayevskiy. New Types of TAOI Centrifugal 125  
Fans  
This article describes ten types of new centrifugal fans. These fans were  
designed by TAOI in 1956-1957 and have a high efficiency coefficient 0.76-0.85.  
It is suggested that some of them might replace less efficient fans now in  
production. The article states that 100,000 fans are currently produced in the  
USSR per year and operation of these fans requires 800,000 kw.

9. Giverniy, A.S. and Ye. Ye. Golobin. Aerodynamic Characteristics of the 135  
Initial Sector of a Circular Section Duct During Turbulent Flow in the  
Boundary Layer  
The authors describe an approximate method for calculating the turbulent  
boundary layer in the initial sector of an annular duct taking account of the  
influence of the transverse curvatures of the internal and external convex and  
concave surfaces of given radiuses on the shape of the velocity profile and  
on other characteristics of the turbulent boundary layer.

10. Giverniy, A.S. and A.S. Giverniy. The Influence of Initial Turbulent Flow 140  
on the Characteristics of Diffuser Ducts  
Results of a theoretical investigation of the influence of initial tur-  
bulentness of flow in the initial sector of a plane diffuser with straight walls  
on diffuser characteristics are given. The calculations show that the coefficient of full pressure losses, efficiency  
coefficient, maximum degree of diffuser expansion, etc.

SOV/24-59-1-7/35

AUTHORS: Ginevskiy, A.S., and Dovzhik, S.A., (Moscow)

TITLE: ~~Experimental Determination of the Pressure Loss in the Rotating Vanes of Axial Compressors~~ (Eksperimental'noye issledovaniye poter' davleniya vo vrashchayushchemsya kolese oseвого kompressora)

PERIODICAL: Izvestiya Akademii Nauk SSSR, Otdeleniye Tekhnicheskikh Nauk, Energetika i Avtomatika, 1959, Nr 1, pp 45-52 (USSR)

ABSTRACT: In this paper, the results are described of experimental investigation of the pressure loss in the rotating vanes of an axial compressor at low circumferential speeds. On the basis of measurement of the total pressure by means of a radial Pitot rake rotating together with the vanes, the structure was investigated of the losses in the space between the rotating vanes and certain quantitative data were obtained which characterise the total magnitude of the complete pressure loss as well as the distribution of the losses along the radius within a wide range of operating regimes. The work was performed on an axial compressor of 600 mm outer diameter, 300 mm inner diameter, delivering air in an axial direction. The vane

Card 1/5

SOV/24.59.1.7/35

## Experimental Determination of the Pressure Loss in the Rotating Vanes of Axial Compressors

profile was altered to give constant circulation along the radius; full details are given of the vane profile. Measurements of total head were made, using a Pitot rake rotating with the vanes and capable of measuring pressure at 18 different radial positions simultaneously, i.e. covering the space between the roots of the blades and the casing. Insufficient detail is given of the method of measurement, manometer connections etc. The equipment allows a complete picture of the total pressure in the region between the blades to be built up and the measurements are expressed in a non-dimensional form.  $\Delta p_0 = p_{01} - p_{02}$  is the total pressure in front of the vane in relative motion;  $p_{02}$  is the total pressure behind the vane.

$$\Delta h = \Delta p_0 / \rho u_R^2 \quad (2)$$

Card 2/5 where  $\rho$  is the air density,  $u_R$  is the circumferential speed at the outer radius of the wheel; the mean value

SOV/24-59-1-7/35

Experimental Determination of the Pressure Loss in the Rotating Vanes of Axial Compressors

of the loss coefficient at a given radius,  $\Delta H$  can be determined by means of the following equation:

$$\Delta H = \frac{1}{\varphi_0} \int_0^{\varphi_0} \Delta h(\varphi) d\varphi \quad \left( \varphi_0 = \frac{2\pi}{z} k \right) \quad (3)$$

where  $k$  is the number of spaces between vanes. Thus, the pressure loss coefficient for all radii for any working condition is given by:

$$\sum \Delta H = \frac{1}{J} \int_{r_0}^1 \Delta H(r) c_a^2(r) r^2 dr ; \quad c_a = \frac{c_a}{u_R}$$

where  $c_a$  is the absolute flow velocity in the vane. Eq (5) expresses the flow rate coefficient  $c_{a0}$  and for a series of  $c_{a0}$  values the theoretical head  $H_T$  is calculated and also the coefficient of the total head  $H$ . The Reynolds number, based on the relative flow

Card 3/5

SOV/24-59-1-7/35

Experimental Determination of the Pressure Loss in the Rotating Vanes of Axial Compressors

velocity in the wheel, is  $2 \times 10^5$ . Fig 2 shows the structure of the head loss  $\Delta h$  over the vanes at different radii, ranging from the vane tip to close to the root. There is much more variation in these extreme regions. Fig 3 shows polar plots of the head loss for different working conditions. Over most of the region  $\Delta h$  is practically zero but increases in the space between successive vanes due to profile loss and friction of air on blade surfaces. There is also some loss over the radial gap between the blade tip and the casing, while at the root section the pressure loss is not only due to friction of the air on the hub surface but also due to the two boundaries formed by the blades and the hub with the associated secondary flow losses. A brief discussion is given of the factors influencing this head loss, mainly concerned with the angle of attack of the blades and the boundary layer thickness. Fig 4 shows the variation of head loss with radius in different working conditions. In conclusion, an attempt is made to

Card 4/5

SOV/24-59-1-7/35

Experimental Determination of the Pressure Loss in the Rotating Vanes of Axial Compressors

divide up the losses which occur over the vane. Fig 5 shows the total  $\sum \Delta H$  divided into the profile loss:  
1) end flow and secondary flow loss; 2) output loss;  
3) it is evident that the profile loss makes up 50 to 55% of the total. Fig 6 shows the efficiency variation with working conditions. There are 6 figures and 6 references of which 2 are Soviet, 1 English and 3 German.

SUBMITTED: 22nd August 1958

Card 5/5

SOV/179-59-2-5/40

AUTHOR: Ginevskiy, A. S. (Moscow)

TITLE: Turbulent Trail and Stream in a Vortex Flow with the Presence of a Longitudinal Pressure Gradient (Turbulentnyye sled i struya v sputnom potoke pri nalichii predel'nogo gradiyenta davleniya)

PERIODICAL: Izvestiya Akademii nauk SSSR OTN, Mekhanika i mashinostroyeniye, 1959, Nr 2, pp 31-36 (USSR)

ABSTRACT: An effect of the pressure gradient on the trail in a flow around a rigid body in the aerodynamical tube is considerable (Fig 1a). Similarly, this effect can be noticeable in the case of a stream (Fig 1b). A method of calculation of the turbulence is described by the author, taking into account the longitudinal pressure gradient. The equation of turbulence in this trail or stream in this case will take a general form (1), where  $x$  and  $y$  - longitudinal and transverse co-ordinates respectively,  $u$  and  $v$  - mean components of the velocity along the axes  $x$  and  $y$  respectively,  $\tau$  - tangent tension,  $\rho$  - density,  $p$  - pressure. The

Card 1/4



SOV/179-59-2-5/40

### Turbulent Trail and Stream in a Vortex Flow with the Presence of a Longitudinal Pressure Gradient

distribution of the tangent tension is given by Eqs (2), (4) and (5). The last two expressions are substituted in the Eqs (6) and (7) which determine the velocity in the trail (or stream) and at the boundary respectively. The simultaneous solution of both equations gives the expression (8). To find the rate of an increase (or decrease) of the velocity (Fig 1), the formula (9) is derived for  $u = U + u_1$  and  $u_m = U + u_{1m}$ . The velocity profile along the axis can be derived from Eq (7), which can be written in the forms Eqs (10) and (11). The latter can be integrated when the relation (12) is determined ( $\delta'$  and  $\delta''$  -- displacement and loss of impulse, respectively). Then the expressions (13) and (14) are obtained ( $V_\infty$  -- velocity of inflow,  $\delta''$  -- loss of impulse behind the body). The coefficient of body resistance, Eq (16) ( $L$  -- characteristic linear dimension), when substituted in the Eq (11), gives the final differential equation (17). This equation can be integrated in the case of the longitudinal gradient when  $U = \text{const}$ , while

Card 2/4

SOV/179-59-2-5/40

## Turbulent Trail and Stream in a Vortex Flow with the Presence of a Longitudinal Pressure Gradient

the relationship of  $\delta$  and  $u_1 m^0$  can be defined as Eq (18) ( $Z_1 = c_x L$  for trail,  $Z_2 = I/1/2\rho U^2$  for stream), which, when substituted into Eq (17) gives the usual differential equation (19). In the case of the trail, the expression (20) can be derived from Eq (19). The value of  $\beta$  is found experimentally. It can be determined from Eqs (21) and (22) for the trail as  $\beta = I/16 \approx 0.197$  and from Eqs (23) and (24) for the stream as  $\beta = 0.035 \pi = 0.11$ . The determination of the profile velocity can be simplified when Eq (25) is applied ( $\kappa$  - experimental constant), which, together with Eq (4), will give the relationship (26). Fig 2 illustrates the comparison of the results obtained from the various formulae: the curves 1, 2, 3 were calculated from Eqs (9), (26) and (28); 4 and 5 - experimental points for the plane turbulent trail and stream, respectively, 6 and 7 - experimental points for the coaxial turbulent trail and stream, respectively. The difference between the theoretical and

Card 3/4

307/179-59-2-5/40

Turbulent Trail and Stream in a Vortex Flow with the Presence of a Longitudinal Pressure Gradient

experimental determination of the velocity profile can be improved by a more exact approximation of the tangent tension, e.g. the Eq (28) can be used for the conditions (3) and  $\tau$  expressed by Eq (27). There are 2 figures and 9 references, of which 7 are Soviet and 2 German.

SUBMITTED: August 22, 1958.

Card 4/4

SOV/179-59-3-40/45

AUTHORS: Ginevskiy, A. S. and Fedyayevskiy, K. K. (Moscow)

TITLE: Some Laws of the Unsteady, Forward Motion of Bodies in a Viscous Liquid (Nekotoryye zakonomernosti pri neustanovivshemsya postupatel'nom dvizhenii tel v vyazkoy zhidkosti)

PERIODICAL: Izvestiya Akademii nauk SSSR, Otdeleniye tekhnicheskikh nauk, Mekhanika i mashinostroyeniye, 1959, Nr 3, pp 207-209 (USSR)

ABSTRACT: The interaction force  $X$  between a body and a liquid can be defined as Eq (1), where  $\rho$ ,  $\mu$  - density and viscosity of a liquid respectively,  $g$  - gravity,  $V$  and  $dV/dt$  - velocity and acceleration of a body,  $L$  - characteristic linear magnitude,  $N_{Re}$  - Reynold's number,  $N_{Fr}$  - Freude number,  $N_W$  - dimensionless acceleration characterizing the relationship of forces of inertia, Eq (2). The actual relationship of  $f_1(N_{Re}, N_{Fr}, N_W)$  and  $f_2(N_W)$  is determined by the shape of a body and by the character of the motion and flow. In the case of laminar motion of a sphere in a viscous liquid, the coefficient of resistance can be shown as Eq (3) or as Eq (5) in a general case ( $L$  - radius of the

Card 1/2

SOV/179-59-3-40/45

## Some Laws of the Unsteady, Forward Motion of Bodies in a Viscous Liquid

sphere). The motion in this case depends on the initial condition, Eq (4), where the ratio  $N_{Re}/N_W$  can be found from Eq (6). Experiments were carried out by the Leningrad Ship Building Institute, where  $\Delta c_x$  was investigated in relation to the parameters  $N_{Re}$  and  $N_W$ . Fig 1 illustrates the results obtained for  $\Delta c_x(N_{Re})$  and  $\Delta c_x(N_W)$  determined for the types of motion characterized by the load P. Fig 2 shows the experimental points of  $\Delta c_x(N_{Re}/N_W)$ . Fig 3 represents the results of the experiments for various velocities and accelerations. It is evident from the experiments that in order to determine the dynamic properties of similar motions of a body in a viscous liquid, the ratio  $N_{Re}/N_W$  or  $N_W$  should be considered in addition to  $N_{Re}$  and  $N_{Fr}$ . There are 3 figures and 5 references, 2 of which are Soviet, 2 English and 1 Italian.

SUBMITTED: November 12, 1958

Card 2/2

GINEVSKIY, A.S.; SOLODKIN, Ye.Ye.

Aerodynamic characteristics of the entrance region of a ring-shaped pipe with turbulent flow in the boundary layer. *Prm. aerodin. no.12:* 155-167 '59. (MIRA 13:1)

(Pipe--Aerodynamics)

SOLODKIN, Ye. Ye.; GINEVSKIY, A.S.

Effect of initial unsteadiness in the flow on characteristics  
of diffusion channels. *Prm. aerodin.* no.12:168-180 '59.

(MIRA 13:1)

(Fluid dynamics)

GINEVSKIY, A.S.

Integral methods for solving problems of a free turbulence.  
Prom.aerodin. no.15:47-71 '59. (MIRA 13:8)  
(Turbulence)



AVDUYEVSKIY, Vsevolod Sergeyevich, dotsent; DANILOV, Yuriy Ivanovich, dotsent; KOSHKIN, Valentin Konstantinovich, prof.; KUFYRIN, Igor' Nikolayevich, dotsent; MIKHAYLOVA, Militsa Mitrofanovna, dotsent; MIKHAYEV, Yuriy Sergeyevich, dotsent; SERGEL', Greg Sergeyevich, dotsent; GINEVSKIY, A.S., kand.tekhn.nauk, red.; SHEKHTMAN, E.A., izdat.red.; ROZHIN, V.P., tekhn.red.

[Fundamentals of heat transfer in aeronautical and rocket equipment] Osnovy teploperedachi v aviatsionnoi i raketnoi tekhnika. Pod obshchei red. V.K.Koshkina. Moskva, Gos. nauchno-tekhn.izd-vo Oborongiz, 1960. 388 p.

(MIRA 14:4)

(Rockets (Aeronautics)) (Airplanes)  
(Artificial satellites) (Heat---Transmission)

PHASE I BOOK EXPLOITATION

SOV/4820

Ushakov, Konstantin Andreyevich, Professor, Iosif Veniamenovich Brusilovskiy, and Aleksandr Romanovich Bushel'

Aerodinamika osevykh ventilyatorov i elementy ikh konstruktsiy (Aerodynamics of Axial-Flow Fans and Elements of Their Structure) Moscow, Gosgortekhnizdat, 1960. 421 p. Errata slip inserted. 2,000 copies printed.

Ed.: Konstantin Andreyevich Ushakov, Professor; Ed. of Publishing House: G.B. D'yakova; Tech. Eds.: S.Ya. Shklyar, and Z.A. Korovenkova.

PURPOSE: This book is intended for workers of scientific research institutes and planning and design institutes of the ore-mining industry, and may be used by the personnel of other organizations concerned with the design and operation of axial-flow fans.

COVERAGE: The authors describe a modern method of the aerodynamic calculation of axial-flow fans and critically review the design of mine-ventilating machines. Their method of profiling bladed rings is said to be a synthesis of the theory of two-dimensional cascades of airfoils, testing data, and of the generalized results of various systematic experimental investigations carried out by the

Card 1/8

Aerodynamics of Axial-Flow Fans (Cont.)

SOV/4820

authors at the Tsentral'nyy aero-gidrodinamicheskii institut (Central Aero-hydrodynamical Institute). Individual chapters were written as follows: K.A. Ushakov, Introduction, Sec. 3 and 6 of Ch. III, Sec. 4 of Ch. VI, and together with A.R. Bushel', Ch. XII (except Sec. 3); I.V. Brusilovskiy, Ch. I (except Sec. 4), Ch. II, Ch. III (except Sec. 2,3, and 6), Ch. IV, V, VI (except Sec. 4), Sec. 3 and 4 of Ch. VII, Ch. VIII (except Sec. 4 and 5), and Ch. X. (except Sec. 3); A.R. Bushel', Ch. VII (except Sec. 3 and 4), Sec. 4 and 5 of Ch. VIII, Sec. 3 of Ch. X, Sec. 3 of Ch. XII, Ch. XIII and Ch. XIV; A.S. Ginevskiy, Sec. 4 of Ch. I; A.A. Dzidziguri, Ch. IX; I.O. Kersten, Ch. XI; A.V. Kolesnikov, Sec. 2 of Ch. III. No personalities are mentioned. There are 107 references: 87 Soviet, 11 German, and 9 English.

TABLE OF CONTENTS:

Foreword	3
Introduction	5

Card ~~2/8~~

Aerodynamics of Axial-Flow Fans (Cont.)

SOV/4820

PART I. AERODYNAMICS OF AXIAL-FLOW FANS

Ch. I. General Information From the Theory of Fans and Cascades of Airfoils	15
1. Bernoulli and Euler equation	15
2. Geometric parameters of a cascade of airfoils and flow parameters	22
3. Zhukovskiy's theorem	29
4. Aerodynamic characteristics of two-dimensional cascades of airfoils	39
Ch. II. Theory of Axial-Flow Fans	
1. Rotor	57
2. Full diagram of a one-stage fan NA + K + SA [guiding vanes + rotor + nozzle vanes]	57
3. Multistage axial-flow fans	64
4. Counter-flow fans	75
	81
Ch. III. Influence of Air Viscosity. Efficiency Coefficient. Fan's Characteristics	
1. Air viscosity. Boundary layer. Reynolds number	86
2. Profile and secondary losses	86
3. Number of blades	91
4. Efficiency coefficient of the cascade and fan	105
	110

Card 3/8

G. ZIVILSKY, A.S.

Report presented at the Conference on Heat and Transfer, Minsk, USSR, 5-10 June 61.

RN-2852  
SA

- 251. S. I. Gilyarov, T. L. Perezhina, Diffusion of Gaseous Particles in the Presence of Precipitates
- 254. I. L. Perezhina, On Heat Transfer in Laminar Flow in the End Part of a Tube
- 255. I. G. Puzosny, Solution of Some Problems With Phase Connections by Operational Calculus
- 256. L. M. Simak, Numerical Solution of Some Problems of Motion of a Liquid in a Variable Viscosity
- 257. S. L. Detsky, On Conformal Transformation of Reflections Fields in Media
- 258. Iu. A. Sanyalovich, Calculation of Heating of Rectangular Bodies According to Technological Conditions
- 259. I. R. Kikh, Relativity of Optimal Relating Values
- 260. V. N. Puzosny, V. M. Kalinin, F. R. Salyan, Theory of Regeneration Heat-Exchanger Design
- 261. Z. I. Tikhonov, On Calculation Method of Heat Transfer Through the Wall at Change of the Aggregation State of One of Media
- 262. A. V. Krasovskiy, N. A. Zaslavskiy, V. I. Kalugin, Regularities of Heating of the Surface of the Sphere by Radiation and Convection Interactions of Homogeneous Fluidized Beds
- 263. G. L. Babitskiy, Peculiarities and Some Problems of Thermal Treatment Interactions of Homogeneous Fluidized Beds
- 264. L. S. Klyachko, Heat and Mass Transfer in Joint Phase and Porous Convection
- 265. Iu. V. Laptin, Heat and Mass Transfer at Turbulent Flow of Gases Through a Gas-Permeable Substance Sample
- 266. A. G. Gerasimov, E. E. Solov'eva, Influence of Convective Character of the Surface on Heat Transfer Rate of Adiabatic Diffusion and Heat
- 267. A. A. Gerasimov, On the Heat and Mass Transfer Theory at Convective Motion of Liquids
- 268. V. I. Subbotin, K. Ya. Zhuravskiy, B. V. Kozlovskiy, Measurement of Temperature-Dependent Parameters in a Liquid Flow
- 269. A. A. Puzosny, On the Theory of Motion and Burnout of a Body (The Stefan Problem)

S/632/61/000/020/001/008  
D234/D308

AUTHORS: Dovzhik, S. A. and Ginevskiy, A. S.

TITLE: Pressure losses in blade rims of an axial infrasonic compressor

SOURCE: Moscow. Tsentral'nyy aero-gidrodinamicheskiy institut, Promyshlennaya aerodinamika. no. 20, 1961. Osevyeye dozvukovyye kompressory statsionarnogo tipa, 5-56

TEXT: The results are given of an experimental investigation of pressure losses in the inlet (directing) device and in the working wheel of the compressor. The structure of pressure losses was studied at stream velocities  $c_a = 40 - 60$  m/sec; the values of loss coefficients for the directing device were plotted against the radius, the axial velocity and the Re number; the power coefficient and the full pressure coefficient of the working wheel against the radius and the flow coefficient. On the basis of these results formulas determining separate components of the losses are impro-

Card 1/2

Pressure losses in ...

S/632/61/000/020/001/008  
D234/D308

ved and more accurate values are found for coefficients occurring there. A method of constructing a pressure characteristic of a stage is described; characteristics of several single-stage compressors determined with its aid are compared with experimental characteristics. It is concluded that the method is suitable as a first approximation. A. I. Morozov and several others are mentioned for their participation in the study, G. Yu. Stepanov for discussion, A. D. Kochergin and Yu. N. Kurzanov for designing part of the equipment. There are 41 figures, 4 tables and 23 references.

Card 2/2

S/262/62/000/008/005/022  
1007/1207

AUTHORS: Blokh, E. L. and Ginevskiy, A. S.

TITLE: The laminar flow around a cascade of circles and its use in solving hydrodynamic problems

PERIODICAL: Referativnyy zhurnal, otdel'nyy vypusk. 42. Silovyye ustanovki, no. 8, 1962, 22, abstract 42.8.121. Collection "Prom. aerodinamika", Moscow, Oborongiz, no. 20, 1961, 89-136

TEXT: A tentative solution is given for the case of flow around a cascade of near-circles; the deviation of the actual resulting contour from an ideal circle does not exceed 0.6% of the radius, even for the limiting case when  $q = 1$  ( $q$  is the ratio of the circle diameter to the distance between the adjacent circles); for  $q = 0.8$  the deviation is less than 0.1%. The authors also give an exact solution for the flow around a limiting cascade of circles which permits the accuracy of the above tentative method to be estimated for the whole range of variation of the ratio  $q$ . With  $q = 1$ , the error in determining the flow velocity is 1.63%. There are 23 figures and 15 tables.

[Abstracter's note: Complete translation.]

Card 1/1



S/632/61/000/020/005/008  
D234/D308

26.2120

AUTHORS: Belotserkovskiy, S. M., Ginevskiy, A. S. and  
Polonskiy, Ya. Ye.

TITLE: Aerodynamical forces acting on the profile grating in  
non-stationary flow

SOURCE: Moscow. Tsentral'nyy aero-gidrodinamicheskii institut.  
Promyshlennaya aerodinamika. no. 20, 1961. Osevyeye  
dozvukovyye kompressory statsionarnogo tipa, 137-167

TEXT: A method of computing the aerodynamical characteristics,  
being a generalization of the method offered by one of the authors  
in a previous publication, is described. The general case is con-  
sidered in which the profiles vibrate in an arbitrary (but equal)  
manner and are deformed at the same time. The only assumptions  
made are those on which the linear theory is based. The solution  
is constructed as a linear combination of vortex chains of arbi-  
trary stagger and step; the intensity of associated vortexes and  
the basic kinematic parameters of the grating varying harmonic-

✓B

Card 1/2

Aerodynamical forces acting ...

S/632/61/000/020/005/008  
D234/D308

ally with time. Formulas for the forces and moments acting on the grating are derived and the method of numerical computation on an electronic computer is described. Graphs of characteristics are given for a wide range of grating parameters and Strukhal's number [Abstracter's note: Name transliterated] for a grating consisting of plates. There are 22 figures.

✓  
B

Card 2/2

S/632/61/000/020/007/008  
D234/D308

AUTHORS: Ginevskiy, A. S. and Solodkin, Ye. Ye.

TITLE: Hydraulic resistance of ring channels

SOURCE: Moscow. Tsentral'nyy aero-gidrodinamicheskiy institut.  
Promyshlennaya aerodinamika, no. 20, 1961. Osevyye  
dozvukovyye kompressory statsionarnogo tipa, 202-215

TEXT: The authors give an approximate solution of the problem of stabilized turbulent flow in pipes having ring-shaped cross-section, for arbitrary values of the ratio of external to internal radius. Well-known solutions for a circular pipe and plane pipe are obtained as limiting cases. Values of empirical constants are determined. The agreement with experimental data is found to be satisfactory. The opinion that data processing with the aid of hydraulic diameter eliminates the effect of the shape of cross-section, is proved to be incorrect. There are 12 figures.

Card 1/1

10771

S/124/62/000/009/009/026  
A001/A101

26 1120  
AUTHORS: Dovzhik, S. A., Ginevskiy, A. S.

TITLE: Pressure losses in blade crown of the axial subsonic compressor

PERIODICAL: Referativnyy zhurnal, Mekhanika, no. 9, 1962, 35, abstract 9B220  
(In collection: "Prom. aerodinamika, no. 20", Moscow, Oborongiz, 1961, 5 - 56)

TEXT: The authors present the results of an experimental investigation of losses in the blade crown of the guidance apparatus and impeller; the investigation was carried out on an experimental compressor at low subsonic velocities. Radial and pitch distribution of losses was investigated for several variants of blading of the guidance apparatus and impeller. Profile losses, secondary and end losses are analyzed. The published empirical formulae for determining losses of various types are critically reviewed and compared with experimental data available. The following formula for determining the sum of the end and secondary losses in the guidance apparatus and impeller is recommended at conditions below separation: X

Card 1/2

Pressure losses in blade crown of...

S/124/62/000/009/009/026  
A001/A101

$$\zeta_k + \zeta_b = \left( \frac{1}{h} m_k + m_b c_y^2 \tau \right) \frac{\cos^2 \alpha_1}{\cos^3 \alpha_m}$$

where  $\bar{h}$  is blade elongation differing from Howell's formula by the values of coefficients  $m_k$  and  $m_b$  (it is recommended  $m_b = 0.016 \div 0.019$  independent of  $R$  and  $m_k = 0.016 \div 0.022$  for conditions self-simulating in  $R$ ; a more precise selection of  $m_k$  depends on additional conditions). The material obtained enables the authors to propose a method of approximate determination of the pressure characteristic of the stage, which agrees satisfactorily with results of testing stages of axial compressors of various types at conditions below separation. Numerous graphs of experimental results are presented. There are 23 references.

N. A. Kolokol'tsov

[Abstracter's note: Complete translation]

Card 2/2

BLOKH, E.L.; GINEVSKIY, A.S.

Free from eddies flow about a circular cascade and the use of  
this flow in calculating fluid-dynamic cascades. Prom.aerodin.  
no.20:89-136 '61. (MIRA 14:12)

(Cascades (Fluid dynamics))

24 4500

S/262/62/000/011/013/030  
1007/1252

AUTHORS Belotserkovskiy, S. M., Ginevskiy, A. S. and Polonskiy, Ya. Ye.  
TITLE The effect of aerodynamic forces on a cascade under nonsteady flow  
PERIODICAL Referativnyy zhurnal, otdel'nyy vypusk. 42. Silovyye ustanovki, no. 11, 1962, 37, abstract 42 11.175. (In collection Prom. aerodynamika, M., Oborongiz, no. 20, 1961, 137-167)  
TEXT: The principles are outlined of a method for computing the aerodynamic characteristics of a flat-plate cascade. The general case is described of spontaneous vibrations of the cascade about a certain mean position. To obtain the nonsteady aerodynamical characteristics of the cascade, dimensionless functions were determined for the components of the inductive velocities of adjacent vortices. The boundary conditions in the problem under consideration are equality to zero of the normal component of relative velocity at each point of the profile. For an approximate solution the vortex layer, continuously distributed over the profile, is replaced by a number of adjacent vortices. The procedure for calculating the cascade on the "Strela" (Arrow) electronic digital computer is described. The required number of adjacent vortices is dictated by the requirements of computational accuracy. Solution of one variant of the problem takes about 5 minutes. Dependence of the coefficients of rotational derivatives on the spacing and depth of the cascade is shown.

VA

Card 1/2

The effect of.

S/262/62/000/011/013/030  
I007/1252

and a marked discrepancy is noted between these results and the data for a single profile. It is also noted that for a spacing factor above 0.5, these coefficients are practically independent of the Strouhal number

[Abstracter's note: Complete translation.]

VA

Card 2/2



h3117  
S/124/62/000/008/009/030  
1006/1242

AUTHORS: Belotserkovskiy, S.M., Ginevskiy, A.S., and  
Polonskiy, Ya.Ye.

TITLE: Aerodynamic forces acting on a net of profiles  
in non steady flow

PERIODICAL: Referativnyy zhurnal, Mekhanika, no.8, 1962, 29,  
abstract 8B176. (In collection: Prom. aerodinamika,  
no.20, M., Oborongiz, 1961, 137-167)

TEXT: Incompressible nonviscous flow past a net of thin  
profiles (plates) is considered. The profiles execute oscilla-  
tions with equal phase, and can be deformed simultaneously. Each  
profile is replaced by a system of continuously distributed

Card 1/4

S/124/62/000/008/009/030  
 I006/I242

Aerodynamic forces acting ...

vortices with a time-dependent intensity. In the customary linear framework of the problem it is assumed that the vortex sheet leaving the profile maintains an invariable position with respect to the oscillating net. The problem is solved numerically, and for this purpose the continuous vortex sheet along the profile contour is replaced by a discrete number of joined vortices. The determination of the circulation amplitude is reduced to the solution of a system of linear algebraic equations. The equation coefficients are functions of the net parameters and of the Strouhal number. The coefficients of lift and moment of the profile are determined by the formulae

$$c_y = c_{y00} + c_{y\alpha} + c_{y\dot{\alpha}} + c_{y\omega} + c_{y\dot{\omega}} + c_{y\Delta} + c_{y\dot{\Delta}}$$

$$m_z = m_{z00} + m_z^{\alpha} + m_z^{\dot{\alpha}} + m_z^{\omega} + m_z^{\dot{\omega}} + m_z^{\Delta} + m_z^{\dot{\Delta}},$$

where  $c_{y00}$  and  $m_{z00}$  - the coefficient of lift and the moment

Card 2/4

S/124/62/000/008/009/030  
I006/I242

Aerodynamic forces acting...

corresponding to steady flow past the net, respectively. The other terms contain coefficients of rotation derivatives corresponding to the rate of change of angle of attack,  $\dot{\alpha}$ , the profile rotation,  $\omega$ , and its deformation,  $\dot{\Delta}$ . Special cases of identical pure rotational oscillations and pure translational oscillations without deformation are considered. Formulae are obtained connecting the amplitudes of the lift and moment coefficients  $c_l^*$  and  $m_x^*$  and the phase shifts  $\epsilon_1$  and  $\epsilon_2$  with the coefficients of rotation derivatives. The change of the angle of attack,  $\Delta\alpha$ , under the influence of a chain of initial vortices in a quasi-steady case of purely translational motion of the profiles is determined. A numerical calculation of aerodynamic characteristics of a net of plates is performed on the electronic digital computer "Strola" according to the formulas obtained, for values of consistency  $\lambda = b/t$  (b- chord, t- pitch of the net) of 0.25, 0.5, 1.0, 1.5, 2.0 and Strouhall numbers  $q = 0, 0.5, 1.0, 1.5, 2.0$  and

Card 3/4

S/124/62/000/008/009/030  
1006/1242

Aerodynamic forces acting...

stagger angle  $\beta$  in the range  $0 - 60^\circ$ . For  $\tau = 0$  the resultant curves coincide with curves for a single oscillating plate. It is shown that the coefficients of rotation derivatives of the profile in the net are essentially different from the coefficients of a single profile and at low consistencies they depend strongly upon the Strouhall number. All the coefficients of forces and moment at  $\tau > 0.5$  are practically independent of the Strouhall number. The considered coefficients of rotational derivatives are practically independent of the angle of attack:  $\alpha = 0 - 10^\circ$ . The phase shift of the lift coefficient  $\epsilon_1$  attains values of the order of  $20 - 50^\circ$  at Strouhall numbers  $q = 1 - 2$  and  $\tau > 0.5$ , whereas the moment coefficient phase shift  $\epsilon_2$  is small. At  $q = 0$ ,  $\epsilon_1 = \epsilon_2 = 0$ .

✓

[Abstracter's note: Complete translation.]

Card 4/4

GINEVSKIY, A.S.; SOLODKIN, Ye.Ye.

Hydraulic resistance of annular channels. Prom.aerodin. no.20:  
202-215 '61. (MIRA 14:12)

(Pipe—Hydrodynamics)

BELOTSERKOVSKIY, Sergey Mikhaylovich; GINEVSKIY, Aron Semenovich;  
POLONSKIY, Yakov Yefimovich; SUVOROVA, I.A., red.; PUKHLIKOVA,  
N.A., tekhn.red.

[Hydrodynamic theory of cascades; aerodynamic power and moment characteristics of cascades of thin profiles] Gidrodinamicheskaya teoriya reshetok; silovye i momentnye aerodinamicheskie kharakteristiki reshetok tonkikh profilei. Moskva, Gos.nauchno-tekhn. izd-vo Oborongiz, 1962. 124 p. (Promyshlennaya aerodinamika, no.22). (MIRA 15:8)  
(Cascades (Fluid dynamics))

FEODOS'YEV, V.I., doktor tekhn. nauk, prof., red.; GINEVSKIY, A.S.,  
kand. tekhn. nauk, red.; KURBAKOVA, I.P., red. izd-va;  
NOVIK, A.Ya., tekhn. red.

[Some problems in mechanics] Nekotorye voprosy mekhaniki; sbornik  
statei. Moskva, Oborongiz, 1962. 203 p. (MIRA 15:12)  
(Mechanics)

SHEYNIN, Viktor Mikhaylovich; OSIMEN, K. P., kand. tekhn.nauk,  
retsensent; GALITSKIY, Yu. V., inzh., retsenent; GINEVSKIY,  
A.S., kand. tekhn. nauk, red.; MOROZOVA, P.B., red.izd-va;  
ORESHKINA, V.I., tekhn. red.

[Weight and transportation efficiency of passenger planes]  
Vesovaia i transportnaia effektivnost' passazhirsikh sa-  
moletov. Moskva, Oborongiz, 1962. :962 p. (MIRA 16:10)  
(Airplanes)



GINEVSKIY, A.S.

Turbulent nonisothermal jet flows of a compressed gas. From aerodin.  
no.23: 11-65 '62. (MIRA 16:4)  
(Jets--Fluid dynamics) (Turbulence)

GINEVSKIY, A.S.

Radial slot jet flowing out from an annular source with a finite diameter.  
Prom.aerodin. no.23:72-79 '62. (MI:A 16:4)  
(Jets--Fluid dynamics)

GINEVSKIY, A.S.

Turbulent jet flows with return currents of the fluid. Prom.aerodin.  
no.23:80-98 '62. (MIRA 16:4)  
(Jets--Fluid dynamics) (Turbulence)

ACCESSION NR: AT3002066

S/2632/62/000/023/0107/0118

AUTHORS: Ilizarova, L.I.; Ginevskiy, A.S.

TITLE: Experimental investigation of a jet in countercurrent flow

SOURCE: Moscow. Tsentral'nyy aero-gidrodinamicheskiy institut. Promyshlennaya aerodinamika, no. 23, 1962. Struynyye techeniya, 107-118

TOPIC TAGS: aerodynamics, hydrodynamics, gas dynamics, fluid dynamics, jet, jet flow, countercurrent flow, counterflow, incompressible flow, Pitot-Prandtl tube, wind-tunnel test, null reading, null method, null-reading method, dynamic-pressure head, static head

ABSTRACT: The paper reports the results of an experimental investigation of the aerodynamic characteristics of an axially-symmetrical jet in a countercurrent flow within a numerical range of the parameter  $m$  (ratio of the free-flow countervelocity divided by the primary-jet velocity at the nozzle exit) of from 0 to 0.4. Velocity ( $V$ ) and pressure ( $P$ ) profiles are obtained in the "initial" mixing region (surrounding the central core of the jet) and the "main" mixing region (farther downstream) of such a jet, also the dependence of the lengths of these regions on the parameter  $m$ . The experiments were performed in a closed wind tunnel with an open working

Card 1/2

ACCESSION NR: AT3002066

section (440-mm diam). Velocities from 13 to 14 m/sec were employed. The jet nozzle (10 and 15 mm diam) was carefully aligned with the direction of the local free flow. Jet velocity: 120-150 m/sec. Three types of Pitot-Prandtl tubes with 3-component heads and T-shaped heads were developed and employed to explore the complex flow in the mixing sheath between the counterflowing jet-core and wind-tunnel flows. The various types of head employed are described and pictured. A disk-shaped static head is also described and depicted. The pressures and magnitudes and directions of the local velocities were measured by a single head which was transported and positioned by a precision coordinate-locator device. All measurements were done by the null method, that is, all readings were performed by equalizing the pressures in the two branch tubes of a U-shaped manometer. The results of the measurements are portrayed graphically, and it is shown how the length of the initial region of the jet is determined as a function of the ratio  $m$ , also the length of the "torch," which is the sum of the lengths of the initial and the main mixing regions of the jet. Orig. art. has 12 figs., 1 tbl., and 1 eq.

ASSOCIATION: none

SUBMITTED: 00

DATE ACQ: 01May63

ENGL: 00

SUB CODE: AI

NO REF SOV: 003

OTHER: 000

Card 2/2

GINEVSKIY, A.S.; MOROZOV, A.I.

Effect of the radial and circumferential irregularity of the flow  
on characteristics of stages of an axial-flow compressor. Prom.-  
aerodin. no.24:63-73 '62. (MIRA 16:7)  
(Compressors--Aerodynamics)

GINEVSKIY, A.S. (Moskva); SOLODKIN, Ye.Ye. (Moskva)

Effect of the transversal surface curvature on the characteristics  
of an isothermal axisymmetric turbulent boundary layer of a  
compressed gas. Izv.AN SSSR.Otd.tekh.nauk.Mekh.i mashinostr.  
no.1:99-110 Ja-F '63. (MIRA 16:2)

(Boundary layer)

GINEVSKIY, A.S. (Moskva)

Approximate motion equations in problems of the theory of turbulent  
jets. Izv.AN SSSR.Mekh. i mashinostr. no.5:134-140 S-0 '63.  
(MIRA 16:12)



GORLIN, Samuil Markovich; SLEZINGER, Isaak Isayevich; GINEVSKIY,  
A.S., red.

[Aeromechanical measurements; methods and instruments]  
Aeromekhanicheskie izmereniia; metody i pribory. Moskva,  
Izd-vo "Nauka," 1964. 720 p. (MIRA 17:8)

RAKHMATULIN, Khalil Akhmedovich; SAGDUMAL, Anvar Yakovlevich;  
BUNINOVICH, Abram Isakovich; ZVEREV, Igor' Nikolayevich.  
PUTYATE, V.I., dots., reitsentent; PANICHKIN, I.A., prof.,  
reitsentent; GINEVSKIY, A.S., kand. tekhn. nauk, red.

[Gas dynamics] Gazovaya dinamika. Moskva, Vysshaya shkola,  
1965. 722 p. (MIRA 18:10)

L 38543-65 EWT(1)/EWP(m)/EWA(d)/FCS(k)/EWA(1) Pd-1

ACCESSION NR: AP5010080

UR/0170/65/008/004/0540/0545

AUTHOR: Ginevskiy, A. S. 18  
B

TITLE: Calculation of hydraulic resistance in channels with and without flow separation

SOURCE: Inzhenerno-fizicheskiy zhurnal, v. 8, no. 4, 1965, 540-545

TOPIC TAGS: hydraulic resistance, channel flow, flow separation, axisymmetrical channel, plane channel, diffuser

ABSTRACT: The author discusses an approach to the calculation of the hydraulic resistance in axisymmetrical and plane channels in which fluid flow with and without separation takes place. Among problems discussed are flows in diffusers, rectilinear stabilized flow in constant cross-section channels, stabilized flow in curvilinear channels, and flow in channels with a potential core. The author mentions 27 recently published papers in some of which he found some erroneous ideas and confused terminology. Orig. art. has: 6 formulas. [AC]

ASSOCIATION: none

Card 1/2

L 11830-66 EWT(1)/EWP(m)/FCS(k)/EWA(1)/EWA(d) GS

ACC NR: AT6001364 SOURCE CODE: UR/0000/65/000/000/0189/0202

AUTHOR: Solodkin, Ye. Yd. (Moscow); Ginevskiy, A. S. (Moscow)

ORG: None

TITLE: Turbulent nonisothermal flow of a viscous compressible gas in the inlet sections of axisymmetric and flat expanding channels with a null pressure gradient

SOURCE: Teplo- i massoperenos. t. 1: Konvektivnyy teploobmen v odnorodnoy srede (Heat and mass transfer. v. 1: Convective heat exchange in an homogeneous medium). Minsk, Nauka i tekhnika, 1965, 189-202

TOPIC TAGS: fluid flow, hydrodynamics, friction coefficient, boundary layer theory

ABSTRACT: In the inlet section of a channel the velocity, the temperature, the Mach number, and other flow parameters are distributed uniformly over the channel cross section. As the distance from the inlet section increases, a boundary layer arises due to the effect of viscous forces on the walls of the channel and there is an isentropic flow core at parts of the section located nearer to the axis. It is assumed also that heat transfer affects the velocity and temperature distributions

Card 1/2

11030-00  
ACC NR: AT6001364

only within the boundary layer. It follows that the velocity, temperature, Mach number, and other flow parameters remain constant across the channel in the flow core. Flow in the boundary layer is assumed to be turbulent. The article proposes to solve the given problem taking into account the effect of the transverse curvature of the surface on the axisymmetrical turbulent boundary layer. There follows an extended mathematical development based on the foregoing assumptions. Results of the calculations are exhibited in the form of curves showing the change in the local coefficient of friction resistance along the axis, the length of the initial section of the channel under various conditions, and change in the local heat transfer coefficient along the axis. Orig. art. has: 30 formulas, 6 figures.

SUB CODE: 20/ SUBM DATE: 31Aug65/ ORIG REF: 003/ OTH REF: 000

jw

Card 2/2

L 24249-66 EWT(1)/EWP(m)/ETC(f)/EPF(n)-2/ENG(m)/EWA(d)/EWP(j)/I/ETC(m)-5/ENR(1)  
ACC NR: AT6006924 SOURCE CODE: UR/0000/65/000/000/0377/0391 75  
EWT(m) ES/WW/GS/RM B+1

AUTHOR: Ginevskiy, A. S.

ORG: none

TITLE: <sup>2/</sup>Heat and mass transfer in a nonisothermal turbulent gas jet of variable composition in a co-directional stream

SOURCE: Teplo- i massoperenos. t. II: Teplo- i massoperenos pri vzaimodeystvii tel s potokami zhidkostey i gazov (Heat and mass transfer. v. 2: Heat and mass transfer in the interaction of bodies with liquid and gas flows). Minsk, Nauka i tekhnika, 1965, 377-391

TOPIC TAGS: heat transfer, mass transfer, turbulent jet, gas dynamics, turbulent boundary layer, gas jet

ABSTRACT: The mathematical development starts from the differential equations of continuity, momentum, energy, and mass transfer for averaged steady state plane or axisymmetric isobaric motion of a two component gas mixture in a turbulent boundary layer:

$$\frac{\partial}{\partial x} (\rho u y') + \frac{\partial}{\partial y} (\rho v_1 y') = 0; \quad (1)$$

$$\rho u \frac{\partial u}{\partial x} + \rho v_1 \frac{\partial u}{\partial y} = \frac{1}{y'} \frac{\partial (\tau y')}{\partial y}; \quad (2)$$

Card 1/3

L 24249-66

ACC NR: AT6006924

0

$$\rho u \frac{\partial H}{\partial x} + \rho v_1 \frac{\partial H}{\partial y} = \frac{1}{y'} \frac{\partial}{\partial y} [(\sigma + \lambda) y']; \quad (3)$$

$$\rho u \frac{\partial z}{\partial x} + \rho v_1 \frac{\partial z}{\partial y} = \frac{1}{y'} \frac{\partial (\gamma y')}{\partial y}. \quad (4)$$

Здесь

$$\tau = \epsilon \frac{\partial u}{\partial y}, \quad \sigma = \frac{\epsilon}{P_t} \frac{\partial}{\partial y} \left( h + P_t \frac{u^2}{2} \right),$$

$$\gamma = \rho D_t \frac{\partial z}{\partial y} = \frac{\epsilon}{P_d} \frac{\partial z}{\partial y}, \quad h = c_p T, \quad (5)$$

$$\lambda = \frac{\epsilon}{P_t} \left( \frac{P_t}{P_d} - 1 \right) (h_1 - h_2) \frac{\partial z}{\partial y}, \quad v_1 = v \left( 1 + \frac{\rho' v'}{\rho v} \right).$$

$$H = h + \frac{u^2}{2}, \quad P_t = \frac{\epsilon c_p}{\lambda_t}, \quad P_d = \frac{\epsilon}{\rho D_t}$$

x, y are coordinates of a rectangular (j = 0) or cylindrical (j = 1) coordinate system; u, v are the components of the velocity along the x and y axes; ρ is the density of the gas mixture; h is the heat content; H is the total heat content; z is the mass concentration of the substance of the jet or one of its components; D<sub>t</sub> is the coefficient of

Card 2/3

L 24249-66

ACC NR: AT6006924

reciprocal diffusion;  $\epsilon$  is the coefficient of turbulent transfer;  $\lambda_g$  is the coefficient of turbulent heat conductivity;  $P_t$  is the turbulent Prandtl number;  $P_d$  is the diffusion Prandtl number;  $c_p$  is the specific heat capacity of the gas mixture at constant pressure;  $T$  is the absolute temperature. The remainder of the article is devoted to a mathematical solution of the above system of equations. The calculation method is said to be applicable to the solution of a wide range of problems in the theory of turbulent gas jets. Orig. art. has: 53 formulas and 5 figures.

SUB CODE: 20/ SUBM DATE: 09Nov65/ ORIG REF: 004

Card 3/3 *dda*



L 46678-66 EWT(1)/EWP(m)

ACC NR: AF6020726

SOURCE CODE: UR/0421/66/000/003/0059/0067

AUTHOR: Ginevskiy, A. S. (Moscow)

ORG: none

TITLE: Calculation of the transition section of a turbulent jet

SOURCE: AN SSSR. Izvestiya. Mekhanika zhidkosti i gaza, no. 3, 1966, 59-67

TOPIC TAGS: turbulent jet, axisymmetric flow, transition flow, flow profile

ABSTRACT: An approximate calculation method is developed for the transition sections of plane and axisymmetric turbulent jets in a co-moving stream. It is shown why earlier methods, based on differentiation between the initial and final sections are not applicable in the transition (mixing) region. The velocity profiles obtained by this method in the transition region turn out to be the same for plane and axisymmetric jets, and can be used to calculate the variation of the jet parameters along the stream axis by using the set of integral equations connecting the angular momentum and the energy. Limiting parameters are defined under which the results coincide with the velocity profile of the main section of the turbulent jet. It is concluded that in first approximation the external boundary of the transition layer is straight and is a continuation of the outer boundary of the outer section. The method is then demonstrated to be suitable for a determination of continuous velocity-profile deformation in the transition region. Orig. art. has: 8 figures and 33 formulas.

SUB CODE: 20/ SUBM DATE: 01Mar65/ ORIG REF: 003/ OTH REF: 002

Card 1/1 h

L 42755-66 ENT(m) IJP(c) RM

SOURCE CODE: UR/0421/66/000/004/0081/0088

ACC NR: AP6030113

AUTHOR: Ginevskiy, A. S. (Moscow); Ilizarova, L. I. (Moscow); Shubin, Yu. M. (Moscow)

ORG: none

TITLE: Investigation of the microstructure of a turbulent jet in a wake flow *61*  
*3*

SOURCE: AN SSSR. Izvestiya. Mekhanika zhidkosti i gaza, no. 4, 1966, 81-88

TOPIC TAGS: fluid mechanics, wake flow, turbulent jet, jet flow, wind tunnel, boundary layer equation

ABSTRACT: The microstructure of the main part of an axisymmetric turbulent jet in a wake flow is investigated experimentally over a wide range of the wake parameter  $m = u_\delta / u_0$  (0.04, 0.21, 0.4, 0.52), where  $u_\delta$  - is the velocity of wake flow and  $u_0$  is the mean velocity at the nozzle exit. Measurements were made with "Disa Elektronik" apparatus (a constant-temperature anemometer) including two amplifiers and a correlator. The velocity profiles of three components of fluctuating velocity and Reynolds stress were measured in the main part of the jet. The values of the mean velocity and two components of fluctuating velocity were measured at a large number of points on the jet axis. The measured profiles of Reynolds stress are compared with corresponding profiles calculated from an experimentally determined mean velocity profile by means of turbulent boundary layer equations. The correlation

Card 1/2

L 43755-55

ACC NR: AP6030113

coefficient of longitudinal components of fluctuating velocity in one section of the jet was measured for two values of  $m$  and the variation of the integral scale of turbulence across the jet was determined. The results obtained here illustrate the effect of the parameter  $m$  on the characteristics of a turbulent jet in wake flow. Orig. art. has: 7 figures and 19 formulas. [AB]

SUB CODE: 20/ SUBM DATE: 27Feb65/ ORIG REF: 005/ OTH REF: 006/ ATD PRESS: 5074

Card 2/2 JS

I. 07166-67 EWP(m)/EWT(1) FDN/WW/JW/WE

ACC NR: AT6034554

SOURCE CODE: UR/2632/66/000/027/0005/0030

AUTHOR: Ginevskiy, A. S. (Candidate of technical sciences)

62  
60  
B+1

ORG: none

TITLE: The method of integral relations in the theory of turbulent jet flows

SOURCE: Moscow. Tsentral'nyy aero-gidrodinamicheskii institut. Promyshlennaya aerodinamika, no. 27, 1966. Struynyye techeniya (Jet streams), 5-30

TOPIC TAGS: turbulent flow, turbulent jet, turbulent mixing, approximation method, isothermal flow, boundary layer

ABSTRACT: An isothermal, turbulent, plane, axisymmetric jet is investigated using Karman-type integral methods. Both the initial and main flow of the jet are analyzed as the jet issues into a wake whose speed is either slower or faster than the jet speed. Also investigated are expanding and converging flows of a radial-slot type jet. The Golubev integral relation for the plane or axisymmetric jet is given by

$$\frac{d}{dx} \int_0^{\delta} \rho u (u_0^{k+1} - u^{k+1}) y^k dy = k(k+1) \int_0^{\delta} \tau u^{k-1} \frac{\partial u}{\partial y} y^k dy.$$

(k=0, 1, 2, ..., ∞).

The analysis starts with a plane turbulent jet where the jet speed  $u_0$  is either

Card 1/4

UDC: 517.3.004.13:532.517.4